


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

The original survey of the Standard Parallel along the south boundary of T5S, R35E was by J. Cooper, under Contract No. 397, approved April 5, 1882. At this corner he set a post, from which a 12" Pine bears N3°E, 9 lks. and a 14" Pine bears N14°W, 31 lks.

Index File No. Z-09



Description of corner evidence found:

No corner monument found.

Bearing trees found:

A 20" stump, 12" high, bears N14°W, 20.5 ft., no marks.

A 19" stump, 14" high, bears N3°E, 5.94 ft. Toe blaze with marks: on piece of wedge cut from stump.

Description of monument and accessories established to perpetuate the original location of this corner:

Set 3.5" aluminum cap on 2 3/8"x30" aluminum pipe rising 12" in mound of rock. Set steel fence post 3.0 ft. north of corner.

Cap is stamped:

SC	
T5S	R35E
<u>S32</u>	<u>S33</u>
RLS 1844	
1984	

New BT's:

A 7" L. Pine bears N14.5°W, 31.1 ft., blazed and scribed: SC T5S R35E S32 BT.

A 6" Fir bears N69.5°E, 36.0 ft., blazed and scribed: SC T5S R35E S33 BT.

Brass LS 1844 disc in lower end of blaze. Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March 1982.

Compass Declination: 19 3/4°E

Witness: Duane Scott

Corner is found on west slope in north edge of clearing above east Sheep Creek.

I hereby certify the above described corner monument and/or accessories was established as described on September 18, 1984.

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*David E. Scott*

OREGON  
JULY 13, 1979  
DAVID E. SCOTT  
1844

Office of..... County of.....  
State of..... I hereby certify that the within instrument was filed in this office  
for record on the..... day of....., 19.....

..... by .....

(DEPUTY)

<b>UNION COUNTY SURVEYOR</b>	
Date Received	<u>10-17-84</u>
Date Filed	<u>10-24-84</u>
By	<u>G. LANGLITZ, DEPUTY</u>
File No.	<u>994-84R</u>