


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. Z-14

History of original corner establishment:
None



Description of corner evidence found:
None.

Description of monument and accessories established to perpetuate the original location of this corner:

Cap is stamped:

Set 2½"x30" aluminum capped aluminum pipe rising 6". No stones available. Set steel fence post 3' north of corner

T5S R35E
<u>W1/16 S34</u>
RLS 1848
1986

New BT's:

an 8½" W. Larch bears N13¼°W, 20.3 ft., blazed & scribed: W1/16 S34 BT.
a 9½" Doug. Fir bears N23¼°E, 28.9 ft., blazed & scribed: W1/16 S34 BT
Painted blazes and attached signs as required in Specifications for Cadastral Surveys, USFS Region 6, March, 1982. Attached ¾" brass washers marked RLS 1848 to blazes.

Compass Declination: 19½°E

Witness: J. Sutton

I hereby certify that the above described corner monument and/or accessories was perpetuated as hereon described on May 26, 1986.

REGISTERED PROFESSIONAL LAND SURVEYOR
<i>B. A. Sutton</i>
OREGON JULY 13, 1979 B. A. SUTTON 1848

UNION COUNTY SURVEYOR
Date Received <u>8-26-86</u>
Date Filed <u>9-10-86</u>
By <u>G. LANGRISH, DEPUTY</u>
File No. <u>136-86 R</u>

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 19.....

See Survey
27-86

..... by
(COUNTY OFFICIAL) (DEPUTY)