

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. X-5


History of original corner establishment:

Corner established in 1882 by H. Gradon, under General Land Office Contract No. 452.

Surveyor General's records state:

Set basalt stone 14 x 12 x 6 inches, 9 inches in the ground for 1/4 sec. cor. marked 1/4 on W. face from which:

A Pine 8" diam. bears S55°E, 157 lks dist. marked 1/4 S BT.
A Pine 4" diam. bears S15°W, 40 lks dist., marked 1/4 S BT.



Description of corner evidence found:

A diligent search was made and no evidence of the corner or its accessories could be found.

Description of monument and accessories I established to perpetuate the original location of this corner: At surveyed point established by single proportion measurements set 2 1/2" x 30" galvanized pipe with brass cap stamped:


Set pipe 24" in ground with mound of stone to cap.

From which:

A Douglas Fir 6" in dia. bears N28°W, 20.6 ft., scribed 1/4 S31 BT.

A Lodge Pole Pine 6" in dia. bears S80°E, 18.5 ft., scribed 1/4 S32 BT.

Attached 54-3 signs to both BTs. Attached brass washer stamped LS 1294 to foot blaze of both BTs. Painted blazes and 6" band around both BTs orange. Attached 54-4 sign to metal fence post 5' South of corner.



I hereby certify the above corner monument was reestablished as herein described on November 1, 1979.

Witnesses: R. Orton
D. Allen



Office of..... County Surveyor..... County of..... Union.....
Oregon
State of....., I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 19...79
..... by
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR

Date Received _____
Date Filed _____
By _____
File No. 665-84 R

☆ GPO—798-276