CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

None set

INDEX FILE No. X-8 DIAGRAM T5S R36E E 1/16 S32

Description of corner evidence found:

Description of monument and accessories I established to perpetuate the original location of this corner: At surveyed point set 2½"x30" galvanized pipe with brass cap stamped: Set pipe 24" in ground with no stones available for mound.

T5S R36EWM E 1/16

 $C \longrightarrow C$

From which:

A L. P. Pine 6" in dia. bears N73^oE, 29.2 ft., scribed CE 1/16 S32 BT.

S32 1979 OR PLS 1294

File No. 668-84R

A L. P. Pine 6" in dia. bears N730W, 18.5 ft., scribed CE 1/16 S32 BT.

Attached 54-3 signs to both BT's. Attached brass washer stamped LS 1294 to foot blaze of both BT's. Painted blazes and 6" band around both BT's orange. Attached 54-2 and 54-4 signs to metal fenct post 5' South of corner. Attached 54-2 and 54-9 signs to metal fence post 5' West of corner.

> I hereby certify the above corner monument was established as herein described.

October 25, 1979

Witnesses: R. Orton

D. Allen

REGISTERED PROFESSIONAL AND SURVEYOR

Office of County Surveyor	County of Union	
State of Oregon , I hereby certify the		this office
for record on the day of	, 19.79.	UNION COUNTY
COUNTY OFFICIAL)	(DEPUTY)	30KAELOX
rm R6-7100-57 (9/71)		Date Received ∴ GPO 749 509
		Date Filed
		By