CERTIFIED RECORD OF LAND CORNER MONUMENTATION

2-9

History of original corner establishments

Original survey by contract No. 452 dated June 16, 1882 The original notes read; From the standard cor to sections 32&33 on the S boundary which is a flat stone 24x36 marked with a I from which;

A fir 30 ins in diam bears N7. W 58 lks dist marked T5S R36E Sec 32 BT.

A fir 24 ins diam bears NF1°E 171ks dist. marked T5S R36E Sec 33 BT. A pine 36" in diam bears S30°E 50 lks dist marked T6S R36E Sec 5 BT. DIAGRAM T5S R36EWM

> **S22.833** T6S S**5 R36EWM**

Description of serner evidence found:

A fir 30" in diam bears N71°E 17 lks dist. with scribe visible A pine 36" in diam bears S30E 35 ft. with scribe visible. Stone could not be found.
We could not make distance to bearing trees check exactly.

REGISTERED OREGON LAND SURVEYOR

> MAY 4, 1956 DAMES G. VOELZ 381

Description of monument and accessories I established to perpetuate the original location of this corner

Set a 2" galvanized pipe 30" long and 22" in the ground with a bronze cap on top and 8" plate welded to bottom. The hole backfilled with stone and tamped soil.

I stamped the disk. From the original corner the original bearing trees are; A fir 30" indiam bears N71°E 17 lks. A pine 36" in diam bear S30E 35 ft.

I set one new bearing tree, A fir 10" in diam bears N2°W 45.3 ft. distance marked with scribe T5S R36E S32 BT.

(distance of new BT to center of tree) I set a steel fence post with USFS sign 54-4 attached and also two National forest boundary signs were placed indicating USFS National forest land to south and east. Bearing tree signs were placed on the BT facing the corner.

T5S R36E S32 S33 T6S S5 R36E ORE LIC 381 1969

State ofOragon	
(COUNTY OFFICIAL)	Date Received
	Date Filed
	Ву
	File No. 674-84