## CERTIFIED RECORD OF LAND CORNER MONUMENTATION

. History of original corner establishment:

Corner established in 1881 by Jacob C.Cooper under General Land Office Contract No. 397. Surveyor General Record states:

Set post for corner from which:

A pine 8 in. diameter bears N53E, 10 links dist.

A pine 7 ins. diameter bears S44E, 35 links dist.

A pine 9 in. diameter bears N50W, 28 links dist.

A fir 8 in. diameter bears \$70W, 42 links dist.

DIAGRAM T4S R37E

35 | 36

2 | 1
T5S R37E

No record of subsequent remonumentation was found in County records. Description of corner evidence found:

ORIGINAL BTS

A spruce 20 in. diameter N45E, 6.8 feet, live vigorous, scribes visible

A lodgepole pine 12 in. diameter \$42E, 21.2 feet, live vigorous, scribes visible

A fir 10 in. diameter S72W, 27.6 feet, a snag, scribes visible

A stump hole N47W, 18.5 feet $\pm$  , pieces of stump with scribes visible

See map of survey dated June 1980.

Description of monument and accessories I established to perpetuate the original location of this corner:

At the mean distance from the four BTs, I set a  $2\frac{1}{2}$  inch x 30 inch iron pipe with brass cap marked as shown 26 inches in the ground from which;


NEW BTs

A 15 inch tamarack bears S5E, 54.9 feet, marked T5S R37E S1 BT

A 10 inch spruce bears \$58W, 29.0 feet, marked T5S R37E \$2 BT

A 17 inch tamarack bears N80W, 57.0 feet, marked T4S R37E S35 BT

Raised mound of stone



OREGON DUANE I. GRIFFITH

Office of.....

REGISTERED

PROFESSIONAL

Brass washer nailed to 8.T.blaze. Used steel tape and magnetic compass with 18° East declination. Measured to center of 8.T.s

State of, I hereby certify that the	within instrument was filed in th	is office
ror record on the day of	, 19	IRMON COURTY
COUNTY OFFICIAL:		SURVEYOR
obout officially	(DEPUTY)	

.. County of.....

Form R6-7100-57 (9/71)