CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

J. C. Cooper conducted the survey of the First Standard Parallel, Township 5 South, Ranges 34, 35, 36, and 37 East, W.M., together with additional Township and Range lines, under GLO contract No. 397 dated July 14, 1881.

Cooper set a post for the corner point, from which:

A fir 12" dia. bears S 10 E 26 lks. dist. A fir 14" dia. bears S 10 W 38 lks. dist. A fir 5" dia. bears N 80 E 7 lks. dist.

A fir 30" dia. bears N 24 W 84 lks. dist.

DIAGRAM 5S T36E T37E PLS 1206 1987

Description of corner evidence found:

None.

Description of monument and accessories I established to perpetuate the

original location of this corner: After a thorough search of the area revealed no

corner evidence, established the proportioned corner point. Set $2\frac{1}{2}$ " x 30" aluminum pipe 24" into the ground, with 24" diastone mound around it. $2\frac{1}{2}$ " dia. aluminum cap mkd. as shown in the corner diagram.

From the corner point: (New BT's)

A 13" dia. Douglas Fir bears N $64\frac{1}{2}$ W at 29.4 ft. mkd. T5S R36E S1 BT.

A 9" Western Larch bears N 29 E at 30.2 ft. mkd. T5S R37E S6 BT. A 7" Western Larch bears S 78 E at 37.1 ft. mkd. T5S R37E S7 BT. A 8" Western Larch bears S 44 W at 31.0 ft. mkd. T5S R36E S12 BT.

Attached U.S.F.S. 54-9 and 54-3 signs to the bearing trees, and painted the blaze and a 6" band around the bearing trees red. Attached a 3/4" dia. brass I.D. washer mkd. PLS 1206, between the B and T scribes. Set a steel fence post 4' West with U.S.F.S. 54-9 sign to it. Used 18½0 declination on a staff compass for readings to the bearing trees, and used a steel tape to measure to a nail set in the side of the bearing trees at the base.

This corner was monumented to U.S.F.S. specifications on May 28, 1987, witnessed by Tom Fisk and Larry McBroom.

	SURVEYOR
	Data Received 5-1-89
Office of County Surveyor County of Union	Date Filed 5-15-89
State of Oregon I hereby certify that the within instrument was filed in this office	BY G. LANGLITZ DEPUTY
for record on the day of	File No. 60 - 89 R
(COUNTY OFFICIAL)	

Form R6-7100-57 (9/71)

PROFESSIONAL LAND SURVEYOR Ames & Hanle OREGON / JAMES D. HANLEY 1206

REGISTERED

\$ GPO--788-276

UNION COUNTY