

T. 5 S., R. 37 E., Willamette Meridian, Oregon

CHAINS

The following field notes describe the remonumentation of certain original corner points, township 5 south, range 37 east, Willamette Meridian, Oregon, as provided for in the Special Instructions, Group Number 1000, Oregon, dated July 13, 1979, "Investigation of Physical Evidence of Corner Positions and Accessories, Followed by Remonumentation of Corner Points, with New Accessories when Needed."

The remonumentation of original corner points was made at the request of the United States Forest Service, in conjunction with their Land Line Location Program.

The mean magnetic declination is 20° E.

Subdivisions, T. 5 S., R. 37 E., Willamette Meridian, Oregon

(Reconunenting corners established by William R. Graden, U. S. Deputy Surveyor, in 1882)

The cor. of secs. 2, 3, 10, and 11, determined at record bearing and distance from the remains of the original bearing trees:

- A saved fir stump, 32 ins. diam., bears N. 30° E., 6 lbs. dist., with healed flange.
- A decayed fir stump, size indeterminate, bears S. 40° E., 17 lbs. dist., no marks visible.
- A root hole, bears S. 25° W., 56 lbs. dist.
- A saved fir stump, 24 ins. diam., bears N. 70° W., 26 lbs. dist., no marks visible.

At the corner point

Set on aluminum post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with aluminum cap and

T 5 S R 37 E
S 2 1/2
3 1/2 x 1 1/2
1982

from which new bearing trees

- A fir, 10 ins. diam., bears N. 36° E., 30 lbs. dist., whd. T58 R37E R1 BT.
- A lodgepole pine, 10 ins. diam., bears S. 33° E., 83 1/2 lbs. dist., whd. T58 R37E R11 BT.
- A fir, 10 ins. diam., bears S. 40° W., 34 lbs. dist., whd. T58 R37E R10 BT.
- A fir, 13 ins. diam., bears N. 64° W., 35 lbs. dist., whd. T58 R37E R3 BT.

Set a steel fence post alongside aluminum post.

**UNION COUNTY
SURVEYOR**

Date Received 9-26-83

Date Filed 11-18-83

By G. LANGLITZ, DEPUTY

File No. 419-83R

NOTE: MICROFICHE CARD IS AVAILABLE IN COUNTY SURVEYOR'S RECORDS.