

T. 5 S., R. 37 E., Willamette Meridian, Oregon

CHAINS

The following field notes describe the remonumentation of certain original corner points, township 5 south, range 37 east, Willamette Meridian, Oregon, as provided for in the Special Instructions, Group Number 1000, Oregon, dated July 13, 1979, "Investigation of Physical Evidence of Corner Positions and Accessories, Followed by Remonumentation of Corner Points, with New Accessories when Needed."

The remonumentation of original corner points was made at the request of the United States Forest Service, in conjunction with their Land Line Location Program.

The mean magnetic declination is 20° E.

Subdivisions, T. 5 S., R. 37 E., Willamette Meridian, Oregon

(Remonumenting corners established by William H. Graden, U. S. Deputy Surveyor, in 1882)

CORNERS

The cor. of secos. 1, 2, 11, and 12, determined at record bearing and distance from the remains of the original bearing trees:

A decayed fir stump, 7 ins. diam., bears N. 79° E., 25 lns. dist., no marks visible.

A root hole, bears S. 63° E., 30 lns. dist., with a down and decayed fir alongside, 24 ins. diam., with healed blane.

A fir, 18 ins. diam., bears S. 32° W., 24 lns. dist., with scribe marks still visible on partially opened blane.

A sawed fir stump, 30 ins. diam., bears N. 35° W., 9 lns. dist., with healed blane.

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with aluminum cap std.

T 5 S R 37 E
S 2 | S 1
S 11 | S 12
1982

from which new bearing trees

A fir, 30 ins. diam., bears N. 23° E., 53 lns. dist., std. TSS R37E S1 BT.

A fir, 21 ins. diam., bears S. 58° E., 53 lns. dist., std. TSS R37E S12 BT.

A fir, 15 ins. diam., bears N. 44° W., 40½ lns. dist., std. TSS R37E S2 BT.

Set a steel fence post alongside aluminum post.

Corner is located 2.70 aro. NW. of gravelled road, 23 lns. wide, bears N. 60° E. and S.

UNION COUNTY SURVEYOR

Date Received 9-26-83

Date Filed 11-18-83

By G. LANGLITZ, DEPUTY

File No. 415-83 R

NOTE: MICROFICHE CARD AVAILABLE IN COUNTY SURVEYOR'S RECORDS.