

T. 5 S., R. 37 E., Willamette Meridian, Oregon

CHAINS

The following field notes describe the remonumentation of certain original corner points, township 5 south, range 37 east, Willamette Meridian, Oregon, as provided for in the Special Instructions, Group Number 1000, Oregon, dated July 13, 1979, "Investigation of Physical Evidence of Corner Positions and Accessories, Followed by Remonumentation of Corner Points, with New Accessories when Needed."

The remonumentation of original corner points was made at the request of the United States Forest Service, in conjunction with their Land Line Location Program.

The mean magnetic declination is 20° E.

Subdivisions, T. 5 S., R. 37 E.,
Willamette Meridian, Oregon

(Remonumenting corners established by William E. Graden,
U. S. Deputy Surveyor, in 1882)

The $\frac{1}{4}$ sec. cor. of secs. 1 and 12, determined at trued bearing and distance from the original bearing stone:

A fir, 30 ins. diam., bears S. 22° E., 143 lbs.
dist., with healed bane.

A fir, 22 ins. diam., bears S. 40° W., 216 lbs.
dist., with illegible scribe marks visible on
partially opened bane.

At the corner point

Set on aluminum post, 28 ins. long, $\frac{3}{4}$ ins. diam., 18
ins. in the ground, to solid rock, in a mound of stones,
4 ft. base, to top, with aluminum cap and.

T 5 S R 37 E
4 8 1
8 7 7
1982

Set a steel fence post alongside aluminum post,

NOTE: MICROFICHE CARD IS AVAILABLE IN COUNTY SURVEYOR'S RECORDS.

UNION COUNTY
SURVEYOR

Date Received 9-26-83

Date Filed 11-18-83

By G. LANGLITZ, DEPUTY

File No. 416-83 R