

T. 5 S., R. 37 E., Willamette Meridian, Oregon

CHAINS

The following field notes describe the remonumentation of certain original corner points, township 5 south, range 37 east, Willamette Meridian, Oregon, as provided for in the Special Instructions, Group Number 1000, Oregon, dated July 13, 1979, "Investigation of Physical Evidence of Corner Positions and Accessories, Followed by Remonumentation of Corner Points, with New Accessories when Needed."

The remonumentation of original corner points was made at the request of the United States Forest Service, in conjunction with their Land Line Location Program.

The mean magnetic declination is 20° E.

Subdivisions, T. 5 S., R. 37 E.,
Willamette Meridian, Oregon

(Remonumenting corners established by William R. Graden,
U. S. Deputy Surveyor, in 1882)

CHAINS

The cor. of secs. 14, 15, 22, and 23, monumented with the original basalt stone, 18 x 18 x 6 ins., firmly set 9 ins. in the ground, no marks visible, from which the remains of the original bearing trees:

A root hole, bears N. 60° E., 11 lbs. dist.

A pine stump, 10 ins. diam., bears S. 25° W., 43 lbs. dist., with scribe mark B visible on decayed base.

A root hole, bears N. 60° W., 6 lbs. dist.

At the corner point

Set an aluminum post, 24 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to solid rock, in a mound of stone, 2 1/2 ft. base, to top, with aluminum cap wkd.

T 5 S R 37 E
S 15 | S 14
S 22 | S 23
1982

from which new bearing trees

A fir, 14 ins. diam., bears N. 66° E., 67 lbs. dist., wkd. T5S R37E S14 NY.

A fir, 12 ins. diam., bears S. 10° E., 31 lbs. dist., wkd. T5S R37E S23 NY.

A lodgepole pine, 9 ins. diam., bears S. 79° W., 1 1/2 lbs. dist., wkd. T5S R37E S22 NY.

A lodgepole pine, 5 ins. diam., bears N. 11° W., 24 lbs. dist., wkd. X NY.

Deposit corner stone and set a steel fence post alongside aluminum post.

**UNION COUNTY
SURVEYOR**

Date Received 9-26-83

Date Filed 11-18-83

By G. LANGLITZ, DEPUTY

File No. 417-83 R

NOTE: MICROFICHE CARD IS AVAILABLE IN COUNTY SURVEYOR'S RECORDS.