

T. 5 S., R. 37 E., Willamette Meridian, Oregon

CHARGE

The following field notes describe the remonumentation of certain original corner points, township 5 south, range 37 east, Willamette Meridian, Oregon, as provided for in the Special Instructions, Group Number 1000, Oregon, dated July 13, 1979, "Investigation of Physical Evidence of Corner Positions and Accessories, Followed by Remonumentation of Corner Points, with New Accessories when Needed."

The remonumentation of original corner points was made at the request of the United States Forest Service, in conjunction with their Land Line Location Program.

The mean magnetic declination is 20° E.

Subdivisions, T. 5 S., R. 37 E.,
Willamette Meridian, Oregon

(Remonumenting corners established by William E. Gordon,
U. S. Deputy Surveyor, in 1882)

The $\frac{1}{4}$ sec. cor. of secs. 14 and 21, remonumented with the original basalt stone, 18 x 12 x 8 ins., firmly set 10 ins. in the ground, mid. $\frac{1}{4}$ on N. face, from which the remains of the original bearing trees:

A root hole, bears S. 30° E., 12 lbs. dist., with a down pine alongside, 12 ins. diam., with scribe marks $\frac{1}{4}$ S 87 visible on open blaze.

A root hole, bears N. 33° W., 6 lbs. dist., with a down pine alongside, 12 ins. diam., with scribe marks $\frac{1}{4}$ S 87 visible on open blaze.

At the corner point

Set an aluminum post, 28 ins. long, $\frac{3}{4}$ ins. diam., 18 ins. in the ground, to solid rock, in a round of stones, $\frac{1}{2}$ ft. base, to top, with aluminum cap and.

T 5 S R 37 E
S 14
R 21
1882

From which new bearing trees

A fir, 23 ins. diam., bears S. 26° W., 37 lbs. dist., mid. $\frac{1}{4}$ S 23 NW.

A fir, 17 ins. diam., bears N. 13° W., 20 lbs. dist., mid. $\frac{1}{4}$ S 14 NW.

Deposit corner stone and set a steel fence post alongside aluminum post.

UNION COUNTY
SURVEYOR

Date Received 9-26-83

Date Filed 11-18-83

By G. LANGLITZ, DEPUTY

File No. 41B-83 R

NOTE: MICROFICHE CARD IS AVAILABLE IN COUNTY SURVEYOR'S RECORDS.