

T. 5 S., R. 37 E., Willamette Meridian, Oregon

CHAINS

The following field notes describe the remonumentation of certain original corner points, township 5 south, range 37 east, Willamette Meridian, Oregon, as provided for in the Special Instructions, Group Number 1000, Oregon, dated July 13, 1979, "Investigation of Physical Evidence of Corner Positions and Accessories, Followed by Remonumentation of Corner Points, with New Accessories when Needed."

The remonumentation of original corner points was made at the request of the United States Forest Service, in conjunction with their Land Line Location Program.

The mean magnetic declination is 20° E.

Subdivisions, T. 5 S., R. 37 E.,  
Willamette Meridian, Oregon

(Remonumenting corners established by William R. Graden,  
U. S. Deputy Surveyor, in 1882)

The ¼ sec. cor. of secs. 13 and 14, monumented with the original basalt stone, 18 x 6 x 6 ins., loosely set 2 ins. in the ground, mid. ¼ on N. face, from which the remains of the original bearing cross:

A fir, 19 ins. diam., bears N. 89° E., 19 lbs.  
dist., with beaded brass.

A fir snag, 15 ins. diam., bears S. 25° W., 32 lbs.  
dist., with square mark 8 visible on partially  
opened brass.

At the corner point

Set an aluminum post, 28 ins. long, 2 ¼ ins. diam., 2 1/2 ins. in the ground, in a collar of stone, with aluminum cap mid.

T 5 S R 37 E

¼ 13

1 24

1982

from which a new bearing tree

A fir, 11 ins. diam., bears S. 35° W., 46 lbs.  
dist., mid. ¼ S24 SW.

Deposit corner stone and set a steel 5/8" post  
alongside aluminum post.

NOTE: MICROFICHE CARD AVAILABLE IN COUNTY SURVEYOR'S RECORDS.

<b>UNION COUNTY SURVEYOR</b>	
Date Received	<u>9-26-83</u>
Date Filed	<u>11-18-83</u>
By	<u>G. LANGLITZ, DEPUTY</u>
File No.	<u>412-83 R</u>