CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

William R. Gradon conducted the survey of Township 5 South, Range 37 East, W.M., under GLO contract No. 445 dated June 1, 1882.

Gradon set a post for the corner point,

from which:

A Pine 6" dia., bears S 85° E at 5 lks. dist. A Pine 7" dia., bears N 75° W at 7 lks. dist.

P-17 DIAGRAM T5S R37E 1/4 S 23 PLS 1206 1987

Description of corner evidence found:

None.

Description of monument and accessories I established to perpetuate the original location of this corner:

After a thorough search of the area revealed no original corner

At the proportioned point, set a $2\frac{1}{2}$ " x 30" aluminum pipe with a $2\frac{1}{5}$ " aluminum cap, 24" into the ground, with a 36" dia. stone mound around it. Cap is marked as shown in the corner diagram.

From the corner point: (New BT's)
A 11" dia. Western Larch bears N 46° W at 35.8 ft. dist., mkd. 1/4 S 22 BT.
A 12" dia. Western Larch bears N 46° E at 21.3 ft. dist., mkd. 1/4 S 23 BT.

Attached U.S.F.S. 64-9 and 64-3 signs to the bearing trees, and painted the face of the blaze and a 6 band around the bearing trees red. Attached a 3/4" dia. brass washer, marked PLS 1206, between the B and T scribes. Set a steel fence post 4' North of the monument and attached a U.S.F.S. 54-9 sign to it. Used $18\frac{1}{2}$ 0 declination on a staff compass for readings to the bearing trees, and used a steel tape to measure to a nail set in the side of the trees at the base.

This corner was monumented to U.S.F.S. specifications on October 22, 1987 witnessed from Fight Toront M.D.

JAMES D. HANLEY 1206

October 22, 1987, witnessed Tom Fisk, Larry McBroom an	d Andy Marlette.
	UNION COUNTY SURVEYOR
	Onto Roceived 5-1-89
Office of County Surveyor County of Union State of Oregon , I hereby certify that the within instrument was filed in to	his office By G. LANGLITZ, DEDUTY
for record on the day of	Ella No. 72-8912
Form R6-7100-57 (9/71) REGISTERED PROFESSIONAL LAND SURVEYOR	<u>·</u> ☆ gPO—798-276
OREGON,	