CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

William R. Gradon conducted the survey of Township 5 South, Range 37 East, W.M., under GLO contract No. 445 dated June 1, 1882.

Gradon set a post for the corner point, from which:

A black pine 14" dia. bears N 60 W at 47 lks. dist. A black pine 4" dia. bears S 45 W at 22 lks. dist. A tamarack 8" dia. bears N 35 E at 120 lks. dist. A black pine 8" dia. bears S 70 E at 72 lks. dist.

R-5 DIAGRAM T5S R37E 30 S 29 PLS 1206 1987

Description of corner evidence found:

8" dia. Western Larch bears N 35 E at 79.2 ft. dist., tree is down and partially rotted. Mkd. T5° /B

No trace of the other three bearing trees.

Description of monument and accessories I established to perpetuate the

original location of this corner: Corner point re-established from the one original found bearing tree.

At the corner point, set $2\frac{1}{2}$ " x 30" aluminum pipe 28" into the ground, with no stone mound. $2\frac{1}{2}$ dia. aluminum cap mkd. as shown in the corner diagram.

From the corner diagram.

From the corner point: (New BT's)

A 16" dia. Spruce bears N 65 W at 23.8 ft. dist. mkd. T5S R37E S19 BT

A 11" dia. Western Larch bears N 23 E At 32.1 ft. dist. mkd. T5S R37E S20 BT

A 6" dia. Lodgepole Pine bears S 69 E at 34.7 ft. dist. mkd. T5S R37E S29 BT

A 11" dia. Spruce bears S 38 W at 51.5 ft. dist. mkd. T5S R37E S30 BT

Attached U.S.F.S. 54-9 and 54-3 signs to the bearing trees, and painted the face of the blaze and a 6" band around the bearing trees red. Attached a 3/4" dia. brass I.D. washer, mkd. PLS 1206 between the B and T scribes. Set a steel fence post 4' West with U.S.F.S. 54-9 sign attached. Used $18\frac{1}{2}$ declination on a staff compass for readings to the bearing trees, and used a steel tape too measure to a nail set in the side of the trees at the base.

This corner was monumented to U.S.F.S. specifications on

September 28, 1987, witnessed by Tom Fisk and Andy Marlette. UNION COUNTY SURVEYOR Data Received 5-1-89 Office of County Surveyor County of Union GLANGLITZ, DEPUTY

State ofOregon, I hereby certify that the within instrument was filed in this office for record on the...... day of...... , 19.....by

(DEPUTY)

Form R6-7100-57 (9/71)

LAND SURVEYOR ames of Henly OREGON SEPTEMBER 23 1977 JAMES D. HANLEY

1206

REGISTERED **PROFESSIONAL**

☆ GPO---798-276