## CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

William R. Gradon conducted the survey of Township 5 South, Range 37 East, W.M., under GLO contract No. 445 dated June 1, 1882.

Gradon set a post for the corner point, from which:

A black pine 6" dia. bears N 34 E at 20 lks.

A black pine 8" dia. bears S 20 E at 18 lks. A black pine 10" dia. bears S 40 W at 25 lks. A black pine 8" dia. bears N 35 W at 20 lks.

R-9 **DIAGRAM** T5S R37E 20 S 21 S 29 S 28 PLS 1206 1987

## Description of corner evidence found:

A 10" dia. dead and standing Lodgepole Pine bears N 34 E 20 lks. mkd. T5S R37E S21 BT

A 12" dia. live Lodgepole Pine bears S 20 E 18 lks. mkd. T5S R37E S28 BT

A root hole bears S 40 W 25 lks.

A down and rotted Lodgepole Pine, size indeterminable, bears N 35 W 20 lks. mkd. BT

Description of monument and accessories I established to perpetuate the

original location of this corner: At the corner point as re-established from the remains of the four original found bearing trees: Set  $2\frac{1}{z}$ " x 30" aluminum pipe 28" into the ground, with a small stone mound around it.  $2\frac{1}{7}$ " dia. aluminum cap is marked as shown in the corner diagram.

From the corner point: (New BT's)
A 7" dia. Spruce bears S 41 W 14.9 ft. dist. mkd. T5S R37E S29 BT

A 8" dia. Spruce bears N 31 W 30.6 ft. dist. mkd. T5S R37E S20 BT A 8" dia. Western Larch bears N 48 E 52.5 ft. dist. mkd. T5S R37E S21 BT

Attached U.S.F.S. 54-9 and 54-3 signs to the bearing trees, and painted the face of the blaze and a 6" band around the bearing trees red. Attached a 3/4" dia. brass I.D. washer, mkd. PLS 1206, between the B and T scribes. Set a steel fence post 4' North with U.S.F.S. 54-9 sign attached. Used  $18\frac{1}{2}$  declination on a staff compass for readings to the bearing trees, and used a steel tape to measure to a nail set in the side of the trees at the base.

This corner was monumented to U.S.F.S. specifications on November 3, 1987, witnessed by Larry McBroom and Andy Marlette.

	UNION COUNTY SURVEYOR
	Data Received 5-1-89
	10th 1716d 5-15-89
Office of County Surveyor County of Union	By G. LANGLITZ DENTY
State of $\dfrac{0\mathtt{regon}}{0}$ , I hereby certify that the within instrument was filed in this	office File No. 75-89 R
for record on the day of, 19	Language and the second

REGISTERED **PROFESSIONAL** Form R6-7100-57 (9/71) LAND SURVEYOR unces of Hanle OREGON SCHLEMBER 23, 1977 JAMES D. HANLEY 1206

☆ GPO---788-276