### CERTIFIED RECORD OF LAND CORNER MONUMENTATION

## History of original corner establishment:

William R. Gradon conducted the survey of Township 5 South, Range 37 East, W.M., under GLO contract No. 445 dated June 1, 1882.

Gradon set a post for the corner point,

from which:

A Pine 12" dia. bears N 50° E at 30 lks. dist. A Pine 14" dia. bears S 75° E at 16 lks. dist. A Pine 12" dia. bears S 25° W at 12 lks. dist. A Pine 14" dia. bears N 10° W at 15 lks. dist.

R-17 DIAGRAM T5S R37E 22 S 27 | S 26 PLS 1206 1987

### Description of corner evidence found:

None.

UNION COUNTY SURVEYOR		
Data Received 5-1-89		
Data Filed 5-15-89		
By G. LANGLITZ DEPUTY		
File No. 79-89 R		

# Description of monument and accessories I established to perpetuate the

original location of this corner: After a thorough search of the area revealed no corner evidence, established the proportioned corner point.

Set a  $2\frac{1}{2}$ " x 30" aluminum pipe with a  $2\frac{1}{2}$ " aluminum cap, 6" below the road surface, with no stone mound. Cap is marked as shown in the corner diagram.

From the corner point: (New BT's)

A 7" dia. Lodgepole Pine bears N 58° W at 25.4 ft. dist., mkd. T5S R37E S 22 BT.

A 18" dia. Western Larch bears N 34° E at 23.5 ft. dist., mkd. T5S R37E S 23 BT.

mkd. T5S R37E S 23 BT. A 8" Lodgepole Pine bears S 10° W at 15.1 ft. dist.,

mkd. T5S R37E S 27 BT.
A 6" dia. Lodgepole Pine bears S 59° E at 34.0 ft. dist.,
mkd. T5S R37E S 26 BT.

Attached U.S.F.S. 54-9 and 54-3 signs to the bearing trees, and painted the face of the blaze and a 6" band around the bearing trees red. Attached a 3/4" dia. brass I.D. washer, marked PLS 1206, between the B and T scribes. Set a steel fence post8.1 South from the monument with U.S.F.S. 54-9 sign attached. Used  $18\frac{1}{2}$  declination on a staff compass for readings to the bearing trees, and used a steel tape to measure to a nail set in the side of the trees at the base.

This corner was monumented to U.S.F.S. specifications on October 22, 1987, witnessed by Tom Fisk, Larry McBroom and Andy Marlette.

for record on the	, I hereby certify that the day of	ty ofUnion within instrument was filed in this office , 19
(COUNTY OFFICIAL)		(DEPUTY)
Form R6-7100-57 (9/71)	REGISTERED PROFESSIONAL LAND SURVEYOR	

must Hay OREGON JAMES D. HANLEY 1206

☆ GPO-798-276