CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

William R Gradon conducted the survey of Township 5 South, Range 37 East, W.M., under GLO contract No. 445 dated June 1, 1882.

Gradon set a post for the corner point,

from which:

A black pine 12" dia. bears N 15 E at 16 lks. A black pine 16" dia. bears S 75 W at 81ks.

R-19 DIAGRAM T5S R37E 26 PLS 1206 1987

Description of corner evidence found:

BT's-

Found rotted tree remains, size indeterminable, bears S 75 W at 5.3 ft. dist. mkd. -

No trace of the other bearing tree.

Corner was relocated from the southwest bearing tree, the blaze was found face down in a position such as to show it being the southwest bearing tree.

Description of monument and accessories I established to perpetuate the

original location of this corner: Corner point re-established from the one original found bearing tree.

At the corner point, set $2\frac{1}{2}$ " x 30" aluminum pipe 24" into the ground with 36" dia. stone mound around it. $2\frac{1}{2}$ " dia aluminum cap mkd. as shown in the corner diagram.

From the corner point: (New BT's)
A 19" dia. Western Larch bears S 25 E at 56.0 ft. dist. mkd. 1/4 S26 BT
A 14" dia. White Fir bears N 35 E at 7.4 ft. dist. mkd. 1/4 S23 BT

Attached U.S.F.S. 54-9 and 54-3 signs to the bearing trees, and painted the face of the blaze and a 6" band around the bearing trees red. Attached 3/4" dia. brass I.D. washer, mkd. PLS 1206, between the B and T scribes. Set a steel fence post 4' West with U.S.F.S. 54-9 sign attached. Used $18\frac{1}{2}$ ° declination on a staff compass for readings to the bearing trees, and used a steel tape to measure to a nail set in the side of the trees at the base.

This corner was monumented to U.S.F.S. specifications on Sente

ember 10, 1907, withessed	by 10m Pisk and Andy Mari	
		UNION COUNTY SURVEYOR
		Data Roceived 5-1-89
		Data El'ad 5-15-89
Office of County Surveyor	a Union	By G. LANGLIZ DAM
State of Oregon , I hereby certi	ify that the within instrument was filed in this	official No. 80-89 R
for record on the day of	, 19	
(COLINTY OFFICIAL)	by	

Form R6-7100-57 (9/71)

REGISTERED **PROFESSIONAL** LAND SURVEYOR

Jamesel Hank OREGON, JAMES D. HANLEY

☆ GPO--798-276