

T. 5 S., R. 37 E., Willamette Meridian, Oregon

CHAINS

The following field notes describe the remonumentation of certain original corner points, township 5 south, range 37 east, Willamette Meridian, Oregon, as provided for in the Special Instructions, Group Number 1000, Oregon, dated July 13, 1979, "Investigation of Physical Evidence of Corner Positions and Accessories, Followed by Remonumentation of Corner Points, with New Accessories when Needed."

The remonumentation of original corner points was made at the request of the United States Forest Service, in conjunction with their Land Line Location Program.

The mean magnetic declination is 20° E.

Subdivisions, T. 5 S., R. 37 E., Willamette Meridian, Oregon

(Remonumenting corners established by William H. Graden, U. S. Deputy Surveyor, in 1882)

The cor. of secs. 23, 24, 25, and 26, monumented with the original basalt stone, 18 x 10 x 8 ins., locally set 8 ins. in the ground, no marks visible, from which the remaining original bearing trees:

A fir, 27 ins. diam., bears N. 40° E., 10 lbs. dist., with healed blaze.

A fir, 17 ins. diam., bears S. 55° W., 20 lbs. dist., with healed blaze. (Healed, S. 60° W.)

A ponderosa pine, 26 ins. diam., bears N. 10° W., 27 lbs. dist., with scribe marks TSS R37E S23 SW visible on open blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2 1/2 ins. dia., 1 1/2 ins. in the ground, to solid rock, in a mound of stone, 3 1/2 ft. base, to top, with aluminum cap mtd.

T 5 S R 37 E
S 23 | S 24
S 25 | S 25
1962

from which a new bearing tree

A fir, 18 ins. diam., bears N. 27° E., 70 lbs. dist., mtd. TSS R37E S24 SW.

Deposit corner stone and set a steel fence post alongside aluminum post.

NOTE: MICROFILM CARD AVAILABLE IN COUNTY SURVEYOR'S RECORDS

UNION COUNTY SURVEYOR

Date Received 9-26-83

Date Filed 11-18-83

By G. LANGLITZ DEPUTY

File No. 411-83 R