CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

William R. Gradon conducted the survey of Township 5 South, Range 37 East, W.M., August 14 to August 25, 1882, under GLO Contract No. 445. Gradon set a basalt stone 18" x 12" x 3", 12" into the ground. Marked $\frac{1}{4}$ on West face, from which:

A Pine, 8" dia., bears N. 50° E. at 40 lks. dist.,

A Pine, 10" dia., bears S. 700 W. at 80 lks. dist.

T-17 DIAGRAM T5S R37E S 27 | S 26 PLS 1206 1987

Description of corner evidence found:

Found a basalt stone 18" x 12" x 3" lying with $\frac{1}{4}$ facing upward.

BT's-

Rotted remains of scribe bears N. 50° E. at 40 lks. dist.

Description of monument and accessories I established to perpetuate the original location of this corner:

In place of the original corner stone, set a $2\frac{1}{2}$ " x 30" aluminum pipe with a $2\frac{1}{2}$ " aluminum cap, 18" into the ground, with a 36" stone mound. Cap is marked as shown in the corner diagram. The original stone was buried 1' North of the monument.

From the corner point: (New BT's) A 10" Spruce bears N. 82° E. at 32.4 ft. dist., mkd. $\frac{1}{4}$ S 26 BT. A 8" Lodgepole Pine bears S. 2° W. at 77.1 ft. dist., mkd. $\frac{1}{4}$ S 27 BT.

Set a steel fence post 4 ft. South from the monument and attached a USFS 54-9 sign. Painted the face of the blaze and a 6" band around the bearing trees red. Attached I.D. washer and USFS 54-9 and 54-3 signs to the bearing trees. Used $18\frac{1}{2}^{0}$ declination on a staff compass for readings to the bearing trees. Used a steel tape to measure to a nail set in the side of the trees. The 3/4" dia. brass I.D. washer mkd. PLS 1206 was nailed between the B and T scribes.

This corner was monumented to USFS specifications on August 13,

1987, witnessed by Larry McBroom and Tim Rouse.

	UNION COUNTY SURVEYOR
	Data Raceived 5-1-89
	1 to 11 od 5-15-69
	By G. LANGLITZ DODUTY
Office of County Surveyor County of Union State of Oregon , I hereby certify that the within instrument was filed in this	File No. 87-89 R
for record on the day of, 19	Application of the control of the co
(COUNTY OFFICIAL) (DEPUTY)	·······

(DEPUTY)

Form R6-7100-57 (9/71)

REGISTERED **PROFESSIONAL** AND SURVEYOR

☆ GPO-708-276

OREGON, JAMES D. HANLEY 1206