

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


V-13

History of original corner establishment:

William R. Gradon conducted the survey of Township 5 South, Range 37 East, W.M., under GLO contract No. 445 dated June 1, 1882.

Gradon set a post for the corner point, from which:

- A black pine 6" dia. bears N 60 E at 17 lks.
- A black pine 6" dia. bears S 35 E at 25 lks.
- A black pine 6" dia. bears S 25 W at 23 lks.
- A black pine 5" dia. bears N 75 W at 15 lks.



Description of corner evidence found:

BT's-

- A 7" dia. sawed and burnt log bears S 35 E at 16.5 ft. dist. mkd. with burnt blaze, and Gradons' usual deep chop marks between the scribing and the BT scribe. The scribing has been totally burnt off.
- A 6" burnt stump bears N 60 E at 11.2 ft. dist. unmarked.
- A nearly completely rotted log, size indeterminable, bears N 75 W at 9.9 ft., tree is too badly rotted to see any scribe.
- No sign of the other BT as it lands in a skid trail.

Description of monument and accessories established to perpetuate the

original location of this corner: Corner point re-established from the three original found bearing trees.

At the corner point, set 2½" x 30" aluminum pipe 26" into the ground, with 36" dia. stone mound around it. 2½" dia. aluminum cap mkd. as shown in the corner diagram.

From the corner point: (New BT's)

- A 5" dia. Lodgepole Pine bears N 11 E at 11.2 ft. dist. mkd. X BT
- A 5" dia. Lodgepole Pine bears S 58 E at 23.2 ft. dist. mkd. X BT
- A 5" dia. Lodgepole Pine bears S 52 W at 18.3 ft. dist. mkd. X BT
- A 4" dia. Lodgepole Pine bears N 28 W at 16.0 ft. dist. mkd. X BT

Attached U.S.F.S. 54-9 and 54-3 signs to the bearing trees, and painted the face of the blaze and a 6" band around the bearing trees red. Attached a 3/4" dia. brass I.D. washer, mkd. PLS 1206, between the B and T scribes. Set a steel fence post 4' West of the monument with U.S.F.S. 54-9 sign attached. Used 18½° declination on a staff compass for readings to the bearing trees, and used a steel tape to measure to a nail set in the side of the trees at the base.

This corner was monumented to U.S.F.S. specifications on September 17, 1987, witnessed by Tom Fisk and Andy Marlette.

UNION COUNTY SURVEYOR	
Date Received	<u>5-1-89</u>
Filed	<u>5-15-89</u>
By	<u>G. LANGRISH, DVM</u>
File No.	<u>91-89 R</u>

Office of County Surveyor..... County of Union
State of Oregon..... I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 19.....

..... by

(DEPUTY)

Form R6-7100-57 (9/71)

