

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


V-17

History of original corner establishment:

William R. Gradon conducted the survey of Township 5 South, Range 37 East, W.M., under GLO contract No. 445 dated June 1, 1882.

Gradon set a post for the corner point, from which :

- A black pine 10" dia. bears N 35 E at 20 lks.
- A black pine 10" dia. bears S 10 E at 15 lks.
- A black pine 10" dia. bears S 40 W at 20 lks.
- A black pine 6" dia. bears N 45 W at 23 lks.



Description of corner evidence found:

None.

UNION COUNTY SURVEYOR	
Date Received	<u>5-1-89</u>
Date Filed	<u>5-15-89</u>
By	<u>G. LANGLITZ, DEPUTY</u>
File No.	<u>93-89 R</u>

Description of monument and accessories established to perpetuate the

original location of this corner: After a thorough search of the area revealed no corner evidence.

At the proportioned point: set a 2½" x 30" aluminum pipe 20" into the ground, with a 36" dia. stone mound around it. 2½" aluminum cap mkd. as shown in the corner diagram.

From the corner point: (Bearing trees)

- A 8" dia. Western Larch bears N 19 E at 12.7 ft. dist. mkd. T5S R37E S26 BT
- A 5" dia. Lodgepole Pine bears N 55 W at 15.0 ft. dist. mkd. X BT
- A 6" dia. Lodgepole Pine bears S 75 W at 27.3 ft. dist. mkd. T5S R37E S34 BT
- A 9" dia. Lodgepole Pine bears S 58 E at 32.1 ft. dist. mkd. T5S R37E S35 BT

Attached U.S.F.S. 54-9 and 54-3 signs to the bearing trees, and painted the face of the blaze, and a 6" band around the bearing trees red. Attached a ¾" dia. brass I.D. washer, mkd. PLS 1206, between the B and T scribes. Set a steel fence post 4' West with USFS 54-9 sign attached. Used 18½° declination on a staff compass for readings to the bearing trees, and used a steel tape to measure to a nail set in the side of the trees at the base.

This corner was monumented to U.S.F.S. specifications on October 23, 1987, witnessed by Tom Fisk, Larry McBroom and Andy Marlette.

Office of...County Surveyor..... County of...Union.....
State of...Oregon....., I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 19.....

..... by
(COUNTY OFFICIAL)

(DEPUTY)

Form R6-7100-57 (9/71)

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

James D. Hanley
OREGON
SEPTEMBER 23, 1877
JAMES D. HANLEY
1206