


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. Z-25

History of original corner establishment:

Original corner established in 1881 by Jacob C. Cooper under contract #397. Set post 4"x4"x4½', 2 ft. in ground. From which:
A 12" Pine bears N24°W, 39 lks.
A 14" Pine bears N40°E, 55 lks.



Description of corner evidence found:

Found decayed post (some scribing visible) in mound of stones. Found the following original bearing trees:
A 14" Lodgepole Pine bears N24°W, 39 lks., tree live, good condition with open blaze, T5SR36ES36BT
A badly decayed pine stump and dead&down tree with slab, axe marks, and faint scribing visible bears N40°E, 55 lks.

Description of monument and accessories established to perpetuate the original location of this corner:

At the location of the original post, I set a 2½"x30" aluminum capped aluminum pipe rising 8" in a mound of stones. Set a steel fencepost 3' north of corner.
Cap is stamped: SC
T5S
R36E R37E
S36|S31
RLS 1848
1987

New BT:

A 5½" Spruce bears N36°E, 22.7 ft., blazed&scribed: T5SR37ES31SCBT
Painted blazes and attached signs as per Standard specifications for Cadastral Surveys, USFS Region 6, March 1982. A ¾" brass disk stamped "RLS 1848" was nailed to the lower end of the blazes.

Corner is 1300 ft. North and 700 ft. West of the intersection of 5125&5125459 on gentle NE'ly slope at the head of a rocky, dry swale that flows NE'ly.

Compass declination: 20°E
Witness: Jeremy Sutton

I hereby certify that the above described corner monument and/or accessories were established as hereon described on June 23, 1987.



UNION COUNTY SURVEYOR

Date Received 8-19-87
Date Filed 8-24-87
by G. LANGRITZ, DEPUTY
File No. 64-87 R

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....
..... by

(COUNTY OFFICIAL)

(DEPUTY)