## CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Jacob C. Cooper conducted the survey of the First Standard Parallel Lines of Township 5 South, Ranges 34, 35, 36 and 37 East, W.M., under GLO contract No. 397, dated July 1, 1881.

Cooper set a post for the corner point,

from which:

A black pine 8" dia. bears N 10 W at 4 lks. A black pine 6" dia. bears N 75 E at 5 lks.

William R. Gradon, under GLO contract No. 445, marked an additional bearing tree:
A black pine 14" dia. bears S 10 W at 40 lks.

Z-9 DIAGRAM T5S **R37E** S 32 S 33 PLS 1206 1987

## Description of corner evidence found:

A down 12" dia. Lodgepole Pine bears S 10 W at 40 lks.

mkd. T6S R37E S5 / BT, on a partially burned blaze.
A 10 dia. Lodgepole Pine stump rotted flush to the ground, bears N 10 W at 4 lks. Rotted and burnt tree remains lay alongside, both unmarked.

## Description of monument and accessories I established to perpetuate the

original location of this corner: Corner point re-established from the found original bearing trees:

At the corner point, set  $2\frac{1}{2}$ " x 30" aluminum pipe 26" into the ground, with 36" dia. stone mound around it.  $2\frac{1}{2}$ " dia. aluminum cap is marked as shown in the corner diagram.

From the corner point: (New BT's)

A 4" dia. Lodgepole Pine bears N 3 W at 12.8 ft. mkd. X BT.

A 4" dia. Lodgepole Pine bears N 76 E at 23.3 ft. mkd. X BT.

Attached U.S.F.S. 54-9 and 54-3 signs to the bearing trees, and the blaze and a 6" band around the bearing trees red. Attached a 3/4" dia. brass I.D. washer mkd. PLS 1206 between the B and T scribes. Set a steel fence post 4' East with U.S.F.S. 54-9 sign Attached to it. Used 18° declination on a staff compass for readings to the bearing trees, and used a steel tape to measure to a nail set in the side of the bearing trees at the base.

9

This corner was monumented to U.S.F.S. specification, 1987, witnessed by Tom Fisk and Andy Marlette.	ions September
	UNION COUNTY SURVEYOR
	Date Received 5-1-89
	Dato Filed 5-15-89
Office of County Surveyor Union	By G. LANGLITZ DOAM
State of Oregon, I hereby certify that the within instrument was filed in this for record on the day of	"File No. 99 - 83 R
(COUNTY OFFICIAL) (DEPUTY)	
Form R6-7100-57 (9/71 REGISTERED PROFESSIONAL LAND SURVEYOR	<b>☆</b> apo—798-276
h = h = h	

mis & Harile OREGON, JAMES D. HANLEY 1206