


Index File No. Z-13 **CORNER RECORD (SEARCH)** (Ref. FSM 7151.4) Tract or Survey No. _____ Cor. S.E. COR. SEC. 33
 T 5S R. 37 E R.D. LA GRANDE County UNION
 Merid. WILLAMETTE N.F. WALLOWA WHITMAN State OREGON

CORNER DIAGRAM



DESCRIBE CORNER MONUMENT FOUND

DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND

Two bearing trees, lodgepole pine. Metal location poster is on the S. corner.

PHOTO IDENTIFICATION DATA

Photo No. _____
 Filed At. _____
 Object Ident. _____
 Ident. By _____
Signature

DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER

Right on Hoodoo Trail and 7 chains west of Webfoot trail.

PLANE COORDINATE POSITION DATA

State _____ Zone _____
 X _____
 Y _____
 Estab. By _____
Agency

Signature
BARNETTE

Title

Division

Headquarters

Date
1/26/27

7100-52-(3.68)

UNION COUNTY SURVEYOR
 Date Received _____
 Date Filed 12-23-87
 By G. LANGLITZ, DEPUTY
 File No. 365-87R


Z-13

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Z-13

History of original corner establishment:

Jacob C. Cooper conducted the survey of the First Standard Parallel Lines of Township 5 South, Ranges 34, 35, 36 and 37 East, W.M., under GLO contract No. 397 dated July 1, 1881.



Cooper set a post for the corner point, from which:

- A black pine 15" dia. bears N 10 W at 39 lks.
- A black pine 12" dia. bears N 39 E at 50 lks.

William R. Gradon, under GLO contract No. 445, marked an additional bearing tree:

- A black pine 14" dia. bears S 5 E at 24 lks.

Description of corner evidence found:

None.

Description of monument and accessories established to perpetuate the original location of this corner:

After a thorough search of the area revealed no corner evidence:

At the proportioned point, set a 2½" x 30" aluminum pipe with a 2½" aluminum cap, 24" into the ground, with no stone mound. Cap is marked as shown in the corner diagram.

From the corner point: (New BT's)

- A 8" dia. Spruce bears N. 69° E. at 22.0 ft. dist., mkd. T5S R37E S34SC BT.
- A 15" dia. Tamarack bears N. 62° W. at 45.3 ft. dist., mkd. T5S R37E S 33 SC BT.

Set a steel fence post 4' South from the monument and attached a USFS 54-9 sign. Painted the face of the blaze and a 6" band around the bearing trees red. Attached I.D. washer and USFS 54-9 and 54-3 signs to the bearing trees. Used 18½° declination on a staff compass for readings to the bearing trees. Used a steel tape to measure to a nail set in the side of the trees. The ¾" brass I.D. washer, mkd. PLS 1206 was nailed between the B and T scribes.

This corner was monumented to USFS specifications on September 15, 1987, witnessed by Larry McBroom and Tim Rouse.

UNION COUNTY SURVEYOR
Data Received <u>5-1-89</u>
Date Filed <u>5-15-89</u>
By <u>G. LANGLITZ, Deputy</u>
File No. <u>101-89 R</u>

Office of _____ County Surveyor _____ County of Union
State of Oregon _____, I hereby certify that the within instrument was filed in this office
for record on the _____ day of _____, 19_____

_____ by _____
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

REGISTERED
PROFESSIONAL
LAND SURVEYOR

James D. Hanley
OREGON
SEPTEMBER 22, 1977
JAMES D. HANLEY
1206