

T. 5 S., R. 37 E., Willamette Meridian, Oregon

The following field notes describe the remonumentation of certain original corner points, township 5 south, range 37 east, Willamette Meridian, Oregon, as provided for in the Special Instructions, Group Number 1000, Oregon, dated July 13, 1979, "Investigation of Physical Evidence of Corner Positions and Accessories, Followed by Remonumentation of Corner Points, with New Accessories when Needed."

The remonumentation of original corner points was made at the request of the United States Forest Service, in conjunction with their Land Line Location Program.

The mean magnetic declination is 20° E.

First Standard Parallel South
T. 5 S., R. 37 E., Willamette Meridian, Oregon

(Remonumenting a corner established by Jacob C. Cooper, U. S. Deputy Surveyor, in 1881, and rehabilitated by William E. Gordon, U. S. Deputy Surveyor, in 1882)

The standard cor. of secs. 34 and 35, on the S. Wdy. of the Tp., determined at record bearing and distance from the remains of the bearing tree estd. by Gordon:

A aged larch stump, 23 ins. diam., bears S. 15° W. 5 lks. dist., with a down larch alongside, with scribe marks S3 visible on open blaze.

At the corner point

Set an aluminum post, 28 ins. long, 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with aluminum cap estd.

S C
T 5 S R 37 E
S 34 1/2 35
1882

from which new bearing trees

A fir, 13 ins. diam., bears S. 43° E., 38 lks. dist., mtd. T58 R37E S35 SC NT.

A fir, 19 ins. diam., bears N. 74° W., 71 lks. dist., mtd. T58 R37E S34 SC NT.

Set a steel fence post alongside aluminum post.

UNION COUNTY
SURVEYOR

Date Received 9-26-83

Date Filed 11-18-83

By G. LANGLITZ, DEPUTY

File No 408-83 R

NOTE: MICROFICHE CARD AVAILABLE IN COUNTY SURVEYOR'S RECORDS.