

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


C-9

History of original corner establishment:

W. B. Barr conducted the survey of Township 5 South, Range 38 East, W.M., under GLO contract No. 388 dated May 7, 1881.

Barr set a basalt rock 24" x 10" x 3" from which:

- A pine 4" dia. bears N 35 W at 74 lks.
- A pine 5" dia. bears N 70 E at 44 lks.



Description of corner evidence found:

Found a stone 22" x 8" x 4", set 16" into the ground, marked with $\frac{1}{4}$ on West face.

BT's-

No trace of original bearing trees.

Description of monument and accessories | established to perpetuate the original location of this corner:

In place of the original corner stone, set a 2 $\frac{1}{2}$ " x 30" aluminum pipe with a 2 $\frac{1}{2}$ " aluminum cap, 14" into the ground, with a 36" stone mound. Cap is marked as shown in the corner diagram. The original stone was buried 1' North of the monument.

From the corner point: (New BT's)

- A 9" dia. White Fir bears N. 30° W. at 50.3 ft. dist., mkd. $\frac{1}{4}$ S 5 BT.
- A 13" dia. Ponderosa Pine bears S. 69° E. at 58.2 ft. dist., mkd. $\frac{1}{4}$ S 4 BT.

Set a steel fence post 4 ft. North from the monument and attached a USFS 54-9 sign. Painted the face of the blaze and a 6" band around the bearing trees red. Attached I.D. washer and USFS 54-9 and 54-3 signs to the bearing trees. Used 18 $\frac{1}{2}$ ° declination on a staff compass for readings to the bearing trees. Used a steel tape to measure to a nail set in the side of the trees. The 3/4" brass I.D. washer mkd. PLS 1206 was nailed between the B and T scribes.

This corner was monumented to USFS specifications on September 24, 1987, witnessed by Tom Fisk and Andy Marlette.

UNION COUNTY SURVEYOR

Date Received 5-1-89

Date Filed 5-15-89

By G. LANGLITZ, DEPUTY

File No. 102-89 R

Office of County Surveyor County of Union

State of Oregon, I hereby certify that the within instrument was filed in this office

for record on the day of , 19

..... by

(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

