

E-11

RG23

Form 9600-9
(December 1979)
(formerly 9180-6)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

23

FIELD NOTES

OF THE

REMONUMENTATION OF CERTAIN ORIGINAL CORNER POINTS,

TOWNSHIP 5 SOUTH, RANGE 38 EAST,

[Blank lined area for field notes]

Of the WILLAMETTE Meridian,
in the State of OREGON

EXECUTED BY

Scott R. McIntyre, Cadastral Surveyor

Under special instructions dated July 13, 19 79, approved July 17, 1979

which provided for the surveys included under U.S. Survey/Group
Number 1000, and assignment instructions dated July 30, 19 82

Survey commenced August 20, 19 82
Survey completed August 31, 19 82

UNION COUNTY SURVEYOR	
Date Received	<u>2-2-84</u>
Date Filed	<u>2-28-84</u>
By	<u>G. LANGLITZ, DEPUTY</u>
File No.	<u>822-84R</u>

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 38 E., Willamette Meridian, Oregon

CHAINS

Corner is located 30 lks. E. of an abandoned logging road, 20 lks. wide, bears N. 55° W. and S. 55° E.

The $\frac{1}{4}$ sec. cor. of secs. 8 and 9, determined at record bearing and distance from the remains of the original bearing trees:

A decayed fir stump, 13 ins. diam., bears S. 4° E., 45 lks. dist., with reverse scribe marks $\frac{1}{4}$ S visible on detached portion of overgrowth.

A root hole, bears S. 87° W., 7 lks. dist., with a down and decayed fir alongside, 24 ins. diam., with scribe marks $\frac{1}{4}$ S visible on decayed blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, in a collar of stone, with aluminum cap mkd.

T 5 S R 38 E
 $\frac{1}{4}$
S 8 | S 9
1982

from which new bearing trees

A fir, 17 ins. diam., bears N. 49° E., 26 lks. dist., mkd. $\frac{1}{4}$ 89 BT.

A fir, 11 ins. diam., bears S. 20° W., 61 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ 88 BT.

Set a steel fence post alongside aluminum post.

Corner is located 40 lks. W. of dirt road, 20 lks. wide, bears NE. and SW.

The $\frac{1}{4}$ sec. cor. of secs. 4 and 9, monumented with the original basalt stone, 15 x 12 x 5 ins., firmly set 8 ins. in the ground, mkd. $\frac{1}{4}$ on W. face, from which the remaining original bearing tree:

A fir, 23 ins. diam., bears S. 27° W., 14 lks. dist., with healed blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, in a collar of stone, with aluminum cap mkd.

T 5 S R 38 E
 $\frac{1}{4}$ S 4
S 9
1982

from which a new bearing tree

A spruce, 10 ins. diam., bears N. 48° W., 5 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ 84 BT.

UNION COUNTY
SURVEYOR

Date received 2-2-84

Date filed 2-28-84

By G. LANGRISH DEPUTY

Map No. 822-84 R

PAGE 2/3

36

UNION COUNTY
SURVEYOR

CHAINS

Date Received 2-2-84Date Filed 2-28-84By G. LAUBLITZ, DEPUTYFile No. 822-84R

PAGE 3/3

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 38 E., Willamette Meridian, Oregon

CHAINS

Deposit corner stone and set a steel fence post
alongside aluminum post.

The cor. of secs. 29, 30, 31, and 32, monumented with the original basalt stone, 10 x 8 x 8 ins., firmly set 5 ins. in the ground, no marks visible, from which the remains of the original bearing trees:

A fir stump, 10 ins. diam., bears N. 54° E., 18 lks. dist., with a down fir alongside, size indeterminate, with scribe marks T5S 29 visible on open blaze. (Record, N. 59° E.)

A root hole, bears S. 32½° E., 17 lks. dist., with a down fir alongside, 5 ins. diam., with scribe marks S32 BT visible on open blaze.

A root hole, bears S. 8° W., 23 lks. dist., with a down larch alongside, 10 ins. diam., with scribe marks S31 BT visible on open blaze.

A root hole, bears N. 65° W., 17 lks. dist., with a down larch alongside, 15 ins. diam., with scribe marks S30 BT visible on open blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, in a collar of stone, with aluminum cap mkd.

T 5 S R 38 E
S 30 | S 29
S 31 | S 32
1982

from which new bearing trees

A lodgepole pine, 5 ins. diam., bears N. 19° E., 34 lks. dist., mkd. T5S R38E S29 BT.

A fir, 22 ins. diam., bears S. 68° E., 19 lks. dist., mkd. T5S R38E S32 BT.

A fir, 10 ins. diam., bears S. 36° W., 21 lks. dist., mkd. T5S R38E S31 BT.

A fir, 11 ins. diam., bears N. 73° W., 30 lks. dist., mkd. T5S R38E S30 BT.

Deposit corner stone and set a steel fence post
alongside aluminum post.

The ¼ sec. cor. of secs. 30 and 31, monumented with the original basalt stone, 16 x 6 x 5 ins., firmly set 12 ins. in the ground, in a collar of stone, no marks visible, from which the remains of an original bearing tree:

A sawed larch stump, 16 ins. diam., bears S. 70° W., 68 lks. dist., with a down larch snag alongside, size indeterminate, with scribe marks ¼ S BT visible on open blaze. (Record, 73 lks.)

At the corner point