

R623

Form 9600-9
(December 1979)
(formerly 9188-6)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

23

FIELD NOTES
OF THE

REMONUMENTATION OF CERTAIN ORIGINAL CORNER POINTS,

TOWNSHIP 5 SOUTH, RANGE 38 EAST,

[Lined area for field notes]

Of the WILLAMETTE Meridian,
in the State of OREGON

EXECUTED BY

Scott R. McIntyre, Cadastral Surveyor

Under special instructions dated July 13, 19 79, approved July 17, 1979

which provided for the surveys included under U.S. Survey/Group
Number 1000, and assignment instructions dated July 30, 19 82

Survey commenced August 20, 19 82
Survey completed August 31, 19 82

UNION COUNTY SURVEYOR	
Date Received	<u>2-2-84</u>
Date Filed	<u>2-28-84</u>
By	<u>G. LANGLITZ, DEPUTY</u>
File No.	<u>821-84 R</u>

~~Remonumentation of Certain Original Corner Points,
T. 5 S., R. 38 E., Willamette Meridian, Oregon~~

~~CLAIMS~~

~~Corner is located 30 lks. E. of an abandoned logging road, 20 lks. wide, bears N. 55° W. and S. 55° E.~~

~~The ¼ sec. cor. of secs. 8 and 9, determined at record bearing and distance from the remains of the original bearing trees:~~

~~A decayed fir stump, 13 ins. diam., bears S. 4° E., 45 lks. dist., with reverse scribe marks ¼ 8 visible on detached portion of overgrowth.~~

~~A root hole, bears S. 87° W., 7 lks. dist., with a down and decayed fir alongside, 24 ins. diam., with scribe marks ¼ 8 visible on decayed blaze.~~

~~At the corner point~~

~~Set an aluminum post, 28 ins. long, 2¼ ins. diam., 22 ins. in the ground, in a collar of stone, with aluminum cap mkd.~~

~~T 5 S R 38 E
¼
S 8 | S 9
1982~~

~~from which new bearing trees~~

~~A fir, 17 ins. diam., bears N. 49° E., 26 lks. dist., mkd. ¼ 89 BT.~~

~~A fir, 11 ins. diam., bears S. 20° W., 61¼ lks. dist., mkd. ¼ 88 BT.~~

~~Set a steel fence post alongside aluminum post.~~

~~Corner is located 40 lks. W. of dirt road, 20 lks. wide, bears NE. and SW.~~

~~The ¼ sec. cor. of secs. 4 and 9, monumented with the original basalt stone, 15 x 12 x 5 ins., firmly set 8 ins. in the ground, mkd. ¼ on N. face, from which the remaining original bearing tree:~~

~~A fir, 23 ins. diam., bears S. 27° W., 14 lks. dist., with healed blaze.~~

~~At the corner point~~

~~Set an aluminum post, 28 ins. long, 2¼ ins. diam., 22 ins. in the ground, in a collar of stone, with aluminum cap mkd.~~

~~T 5 S R 38 E
¼
S 4 | S 9
1982~~

~~from which a new bearing tree~~

~~A spruce, 10 ins. diam., bears N. 48° W., 3¼ lks. dist., mkd. ¼ 84 BT.~~

UNION COUNTY
SURVEYOR

Date received 2-2-84

Date filed 2-28-84

By G. LANGUITZ, DEPUTY

File No. 821-84 R

PAGE 2/2