

R023

Form 9600-9
(December 1979)
(formerly 9100-6)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL.

23

FIELD NOTES
OF THE

REMONUMENTATION OF CERTAIN ORIGINAL CORNER POINTS,

TOWNSHIP 5 SOUTH, RANGE 38 EAST,

[Lined area for field notes]

Of the WILLAMETTE Meridian,
in the State of OREGON

EXECUTED BY

Scott R. McIntyre, Cadastral Surveyor

Under special instructions dated July 13, 19 79, approved July 17, 1979

_____ which provided for the surveys included under U.S. Survey/Group
Number 1000, and assignment instructions dated July 30, 19 82

Survey commenced AUGUST 20, 19 82
Survey completed AUGUST 31, 19 82

UNION COUNTY SURVEYOR	
Date Received	<u>2-2-84</u>
Date Filed	<u>2-28-84</u>
By	<u>G. LANGLITZ, DEPUTY</u>
File No.	<u>805-84 R</u>

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 38 E., Willamette Meridian, Oregon

CHAIN

A ponderosa pine, 24 ins. diam., bears S. 50° E.,
18 lks. dist., with healed blaze.

A decayed fir stump, 24 ins. diam., bears S. 45° W.,
24 lks. dist., no marks visible.

A ponderosa pine snag, 10 ins. diam., bears
N. 50° W., 35 lks. dist., with scribe marks
TSS R37E S13 BT visible on open blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 23
ins. in the ground, in a collar of stone, with aluminum
cap mkd.

T 5 S
R 37 E R 38 E
S 13 | S 18
S 24 | S 19
1982

from which new bearing trees

A ponderosa pine, 20 ins. diam., bears N. 74° E.,
21 lks. dist., mkd. TSS R38E S18 BT.

A ponderosa pine, 20 ins. diam., bears S. 70° W.,
41 lks. dist., mkd. TSS R37E S24 BT.

A fir, 13 ins. diam., bears N. 32½° W., 55½ lks.
dist., mkd. TSS R37E S13 BT.

Set a steel fence post alongside aluminum post.

The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of
the Tp., determined from the remains of the original
bearing trees:

A larch, 20 ins. diam., bears S. 60° W., 24 lks.
dist., with scribe mark S visible on partially
opened blaze. (Record, S. 70° W.)

A decayed larch stump, size indeterminate, bears
N. 20° W., 8 lks. dist., with a down and decayed
larch alongside, 10 ins. diam., with scribe marks
T BT visible on open and decayed blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 24
ins. in the ground, with aluminum cap mkd.

T 5 S
R 37 E R 38 E
S 12 | S 7
S 13 | S 18
1982

from which new bearing trees

A fir, 6 ins. diam., bears N. 31° E., 11 lks.
dist., mkd. TSS R38E S7 BT.

A hemlock, 8 ins. diam., bears S. 65° E., 12½
lks. dist., mkd. TSS R38E S18 BT.

UNION COUNTY
SURVEYOR

Date Received 2-2-84

Date Filed 2-28-84

By G. LANGLITZ, Deputy

File No. 805-84R

Page 2/3

UNION COUNTY
SURVEYOR

3

27

Date Received 2-2-84

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 38 E., Willamette Meridian, Oregon

Date Filed 2-28-84

By G. LANGLITZ DEPTM

File No. 805-84R

A fir, 7 ins. diam., bears N. 46° W., 18½ lks.
dist., mkd. T5S R37E S12 BT.

Set a steel fence post alongside aluminum post.

PAGE 3/3

The ¼ sec. cor. of secs. 7 and 12, on the W. bdy. of the
Tp., determined at record bearing and distance from the
remaining original bearing tree:

A fir, 15 ins. diam., bears N. 15° E., 14 lks.
dist., with scribe mark S visible on partially
opened blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 22
ins. in the ground, in a collar of stone, with aluminum
cap mkd.

T 5 S
R 37 E R 38 E
¼
S 12 | S 7
1982

from which a new bearing tree

A spruce, 25 ins. diam., bears S. 37° W., 55 lks.
dist., mkd. ¼ S12 BT.

Corner is located on E. bank of dry creek bed, course S.

Subdivisions, T. 5 S., R. 38 E.,
Willamette Meridian, Oregon

(Remonumenting corners established by William B. Barr,
U. S. Deputy Surveyor, in 1881)

The cor. of secs. 11, 12, 13, and 14, determined from the
remains of the original bearing trees:

A root hole, bears N. 38° E., 32 lks. dist., with
a down pine alongside, 10 ins. diam., with
illegible scribe marks visible on opened and
decayed blaze. (Record, N. 47° E.)

A decayed pine stump, 20 ins. diam., bears S. 48° E.,
60 lks. dist., with scribe marks S BT visible on
weathered and open blaze.

A decayed larch stump, 12 ins. diam., bears
S. 51° W., 86 lks. dist., no marks visible.

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 24
ins. in the ground, with aluminum cap mkd.

T 5 S R 38 E
S 11 | S 12
S 14 | S 13
1982