

J-5

R623

ORIGINAL

23

Form 9400-9
(December 1979)
(January 9400-6)

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

RECOMMENDATION OF CERTAIN ORIGINAL CORNER POINTS.

TOWNSHIP 5 SOUTH, RANGE 38 EAST.

WILLAMETTE
Oregon

EXECUTED BY

Scott B. McIntyre, Cadastral Surveyor

Under special instructions dated July 13, 1979, approved July 17, 1979

Number 1000, which provided for the surveys included under U.S. Survey/Group _____, and assignment instructions dated July 30, 1982.

SCHEME 29

Ames 31 — 19 82

UNION COUNTY SURVEYOR

Date Received 2-2-84

Date Filed 2-28-84

By G. LANGLITZ, DEPUTY

File No. 831-84 R

40

~~Recommendation of Certain Original Corner Points,
T. 5 S., R. 38 E., Willamette Meridian, Oregon~~

MAIN

CHAINED

~~Set a file, 12 ins. long, 6 ins. below surface of dirt road, 15 lins. wide, bears E. and W.~~

~~from which a reference monument~~

~~An aluminum post, 28 ins. long, $\frac{3}{4}$ ins. diam., set 12 ins. in the ground, to solid rock, in a mound of stone, 4 ft. base, to top, for a reference monument, bears North, 38 lbs. dist., with aluminum cap mhd. T5S R38E 4 S17 25 FT TO COR 1962 and an arrow pointing to the corner.~~

~~Set a steel fence post alongside aluminum post.~~

AC
Set
ins
cog

600

~~The cor. of secs. 7, 8, 17, and 18, determined at record bearing and distance from the remains of the original bearing trees:~~

A decayed pine stump, size indeterminate, bears N. 86° E., 13 lins. dist., no marks visible.

A pine snag, 10 ins. diam., bears S. 63° E., 8 lins. dist., with scribe marks S17 BT visible on open blaze.

A larch, 15 ins. diam., bears S. 63° W., 20 lins. dist., with healed blaze.

A pine snag, 10 ins. diam., bears N. 34° W., 32 lins. dist., with scribe marks S7 BT visible on open blaze.

At the corner point

Set an aluminum post, 28 ins. long, $\frac{3}{4}$ ins. diam., 23 ins. in the ground, with aluminum cap mhd.

T	S	R	38	E
8	7	5	8	
8	17	S	17	
1962				

from which new bearing trees

A spruce, 29 ins. diam., bears N. 22° E., 56 lins. dist., mhd. T5S R38E 58 BT.

A fir, 10 ins. diam., bears S. 70° E., 44 lins. dist., mhd. T5S R38E S17 BT.

A spruce, 6 ins. diam., bears N. 53° W., 25 $\frac{1}{2}$ lins. dist., mhd. T5S R38E S7 BT.

Set a steel fence post alongside aluminum post.

Corner is located 45 lins. N. of dry creek bed, course E.

Cen
cen
Th
be
beAC
24
14

61

~~The 4 sec. cor. of secs. 8 and 17, determined at the center of a root hole, with the remains of the original corner tree alongside, a fir, 14 ins. diam., with scribe mark S visible on opened blaze, from which the remains of the original bearing trees:~~

~~A spruce, 28 ins. diam., bears S. 43° W., 30 lins. dist., with healed blaze.~~