

34

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 38 E., Willamette Meridian, Oregon

A ponderosa pine snag, 10 ins. diam., bears
N. 30° W., 33 lks. dist., with scribe mark S
visible on opened blaze. (Record, W. 28° W.)

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 20
ins. in the ground, to solid rock, in a mound of stone,
3 ft. base, to top, with aluminum cap mkd.

T 5 S R 38 E
S 17 | S 16
S 20 | S 21
1982

from which new bearing trees

A ponderosa pine, 10 ins. diam., bears N. 45° E.,
59 lks. dist., mkd. T58 R38E S16 BT.

A ponderosa pine, 18 ins. diam., bears S. 84° E.,
38 lks. dist., mkd. T58 R38E S21 BT.

A ponderosa pine, 10 ins. diam., bears N. 10½° W.,
31½ lks. dist., mkd. T58 R38E S17 BT.

The cor. of secs. 8, 9, 16, and 17, monumented with the
original basalt stone, 14 x 12 x 6 ins., firmly set 9
ins. in the ground, no marks visible, from which the
remains of the original bearing trees:

A fir, 12 ins. diam., bears N. 27° E., 5 lks.
dist., with illegible scribe marks visible on
opened blaze.

A fir snag, 10 ins. diam., bears S. 22° E., 6 lks.
dist., with healed blaze.

A ponderosa pine snag, 12 ins. diam., bears
S. 50° W., 8 lks. dist., with scribe marks S17
BT visible on open blaze. (Record, 15 lks.)

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 22
ins. in the ground, in a collar of stone, with aluminum
cap mkd.

T 5 S R 38 E
S 8 | S 9
S 17 | S 16
1982

from which new bearing trees

A fir, 10 ins. diam., bears S. 49° E., 37½ lks.
dist., mkd. T58 R38E S16 BT.

A fir, 11 ins. diam., bears S. 50° W., 123½ lks.
dist., mkd. T58 R38E S17 BT.

A fir, 13 ins. diam., bears N. 29° W., 51 lks.
dist., mkd. T58 R38E S8 BT.

Deposit corner stone and set a steel fence post
alongside aluminum post.

UNION COUNTY
SURVEYOR

Date Received 2-2-84

Date Filed 2-28-84

By G. LANGLITZ DEPUTY

File No. 820-84R

Page 2/3

UNION COUNTY
SURVEYOR

11

35

Date Received 2-2-84

Date Filed 2-28-84

By G. LANGLITZ CHAINS DEPUTY

File No. 820-84 R

PAGE 3/3

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 38 E., Willamette Meridian, Oregon

Corner is located 30 lks. E. of an abandoned logging
road, 20 lks. wide, bears N. 55° W. and S. 55° E.

The $\frac{1}{4}$ sec. cor. of secs. 8 and 9, determined at record
bearing and distance from the remains of the original
bearing trees:

A decayed fir stump, 13 ins. diam., bears S. 4° E.,
45 lks. dist., with reverse scribe marks $\frac{1}{4}$ S
visible on detached portion of overgrowth.

A root hole, bears S. 87° W., 7 lks. dist., with
a down and decayed fir alongside, 24 ins. diam.,
with scribe marks $\frac{1}{4}$ S visible on decayed blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22
ins. in the ground, in a collar of stone, with aluminum
cap mkd.

T 5 S R 38 E
 $\frac{1}{4}$
S 8 | S 9
1982

from which new bearing trees

A fir, 17 ins. diam., bears N. 49° E., 26 lks.
dist., mkd. $\frac{1}{4}$ S9 BT.

A fir, 11 ins. diam., bears S. 20° W., 61 $\frac{1}{2}$ lks.
dist., mkd. $\frac{1}{4}$ S8 BT.

Set a steel fence post alongside aluminum post.

Corner is located 40 lks. W. of dirt road, 20 lks. wide,
bears NE. and SW.

The $\frac{1}{4}$ sec. cor. of secs. 4 and 9, monumented with the
original basalt stone, 15 x 12 x 5 ins., firmly set 8
ins. in the ground, mkd. $\frac{1}{4}$ on N. face, from which the
remaining original bearing tree:

A fir, 23 ins. diam., bears S. 27° W., 14 lks.
dist., with healed blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22
ins. in the ground, in a collar of stone, with aluminum
cap mkd.

T 5 S R 38 E
 $\frac{1}{4}$ S 4
S 9
1982

from which a new bearing tree

A spruce, 10 ins. diam., bears N. 48° W., 5 $\frac{1}{2}$ lks.
dist., mkd. $\frac{1}{4}$ S4 BT.