

RC23

Form 9600-9
(December 1979)
(formerly 9188-6)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

23

FIELD NOTES

OF THE

REMONUMENTATION OF CERTAIN ORIGINAL CORNER POINTS,

TOWNSHIP 5 SOUTH, RANGE 38 EAST,

Of the WILLAMETTE Meridian,
in the State of OREGON

EXECUTED BY

Scott R. McIntyre, Cadastral Surveyor

Under special instructions dated July 13, 19 79, approved July 17, 1979

_____, which provided for the surveys included under U.S. Survey/Group
Number 1000, and assignment instructions dated July 30, 19 82

Survey commenced August 20, 19 82
Survey completed August 31, 19 82

**UNION COUNTY
SURVEYOR**

Date Received 2-2-84
Date Filed 2-28-84
By G. LANGLITZ, DEPUTY
File No. 804-84R

T. 5 S., R. 38 E., Willamette Meridian, Oregon

CHAINS

The following field notes describe the remonumentation of certain original corner points, township 5 south, range 38 east, Willamette Meridian, Oregon, as provided for in the Special Instructions, Group Number 1000, Oregon, dated July 13, 1979, "Investigation of Physical Evidence of Corner Positions and Accessories, Followed by Remonumentation of Corner Points, with New Accessories when Needed".

The remonumentation of original corner points was made at the request of the United States Forest Service, in conjunction with their Land Line Location Program.

The mean magnetic declination is 20° E.

West Boundary, T. 5 S., R. 38 E.,
Willamette Meridian, Oregon

(Remonumenting corners established by
Timothy W. Davenport, U. S. Deputy Surveyor, in 1862)

The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., determined at record distance from the remains of the original bearing trees:

A fir, 20 ins. diam., bears N. 50° E., 25 lks. dist., with healed blaze.

A saved fir stump, 18 ins. diam., bears N. 56° W., 41 lks. dist., no marks visible. (Record, N. 50° W.)

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, in a collar of stone, with aluminum cap mkd.

T 5 S
R 37 E R 38 E
S 24 | S 19
S 25 | S 30
1982

from which new bearing trees

A fir, 23 ins. diam., bears S. 48° E., 74 lks. dist., mkd. T58 R38E S30 BT.

A fir, 22 ins. diam., bears S. 39½° W., 7½ lks. dist., mkd. T58 R37E S25 BT.

A fir, 20 ins. diam., bears N. 71° W., 80½ lks. dist., mkd. T58 R37E S24 BT.

Set a steel fence post alongside aluminum post.

The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., determined at record bearing and distance from the remains of the original bearing trees:

A root hole, bears N. 60° E., 8 lks. dist., with a down and decayed pine alongside, 14 ins. diam., with illegible scribe marks visible on decayed blaze.

UNION COUNTY
SURVEYOR

Date Received 2-2-84

Date Filed 2-28-84

By G. LANGLITZ, DEPUTY

File No. 804-84 R

FIELD NOTE PAPER

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 38 E., Willamette Meridian, Oregon

CHAIN

A ponderosa pine, 24 ins. diam., bears S. 50° E.,
18 lks. dist., with healed blaze.

A decayed fir stump, 24 ins. diam., bears S. 45° W.,
24 lks. dist., no marks visible.

A ponderosa pine snag, 10 ins. diam., bears
N. 50° W., 35 lks. dist., with scribe marks
T5S R37E S13 BT visible on open blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 23
ins. in the ground, in a collar of stone, with aluminum
cap mkd.

T 5 S
R 37 E R 38 E
S 13 | S 18
S 24 | S 19
1982

from which new bearing trees

A ponderosa pine, 20 ins. diam., bears N. 74° E.,
21 lks. dist., mkd. T5S R38E S18 BT.

A ponderosa pine, 20 ins. diam., bears S. 70° W.,
41 lks. dist., mkd. T5S R37E S24 BT.

A fir, 13 ins. diam., bears N. 32½° W., 55½ lks.
dist., mkd. T5S R37E S13 BT.

Set a steel fence post alongside aluminum post.

The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of
the Tp., determined from the remains of the original
bearing trees:

A larch, 20 ins. diam., bears S. 60° W., 24 lks.
dist., with scribe mark S visible on partially
opened blaze. (Record, S. 70° W.)

A decayed larch stump, size indeterminate, bears
N. 20° W., 8 lks. dist., with a down and decayed
larch alongside, 10 ins. diam., with scribe marks
T BT visible on open and decayed blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 24
ins. in the ground, with aluminum cap mkd.

T 5 S
R 37 E R 38 E
S 12 | S 7
S 13 | S 18
1982

from which new bearing trees

A fir, 6 ins. diam., bears N. 31° E., 11 lks.
dist., mkd. T5S R38E S7 BT.

A hemlock, 8 ins. diam., bears S. 65° E., 12½
lks. dist., mkd. T5S R38E S18 BT.

UNION COUNTY
SURVEYOR

Date Received 2-2-84

Date Filed 2-28-84

By G. LANGLITZ, DEPUTY

File No. 804-84 R

PAGE 3/3