

N-5

RG23

Form 9600-9  
(December 1979)  
(formerly 9100-6)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

23

# FIELD NOTES

OF THE

REMONUMENTATION OF CERTAIN ORIGINAL CORNER POINTS,

TOWNSHIP 5 SOUTH, RANGE 38 EAST,

[Lined area for field notes]

Of the WILLAMETTE Meridian,  
in the State of OREGON

### EXECUTED BY

Scott R. McIntyre, Cadastral Surveyor

Under special instructions dated July 13, 19 79, approved July 17, 1979

which provided for the surveys included under U.S. Survey/Group  
Number 1000, and assignment instructions dated July 30, 19 82

Survey commenced AUGUST 20, 19 82  
Survey completed AUGUST 31, 19 82

<b>UNION COUNTY SURVEYOR</b>	
Date Received	<u>2-2-84</u>
Date Filed	<u>2-28-84</u>
By	<u>G. LANGUITZ, DEPUTY</u>
File No.	<u>829-84R</u>

Reconumentation of Certain Original Corner Points,  
T. 5 S., R. 38 E., Willamette Meridian, Oregon

CLAIMS

from which a new bearing tree

A ponderosa pine, 13 ins. diam., bears N. 84½° W.,  
69½ lks. dist., mkd. T58 R38E S19 NT.

Deposit corner stone and set a steel fence post  
alongside aluminum post.

The cor. of secs. 17, 18, 19, and 20, determined at record  
bearing and distance from which the remains of the orig-  
inal bearing trees:

A root hole, bears N. 50° E., 68 lks. dist., with  
a down pine alongside, 24 ins. diam., with scribe  
marks T58 R38E S17 NT visible on open blaze.

A root hole, bears S. 64° E., 50 lks. dist., with  
a down and decayed pine alongside, size indeter-  
minate, no marks visible.

A root hole, bears N. 47° W., 43 lks. dist.

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 15  
ins. in the ground, to solid rock, in a mound of stone,  
¾ ft. base, to top, with aluminum cap mkd.

T 5 S R 38 E  
S 18 | S 17  
S 19 | S 20  
1982

from which new bearing trees

A fir, 11 ins. diam., bears N. 69° E., 78 lks.  
dist., mkd. T58 R38E S17 NT.

A fir, 20 ins. diam., bears S. 82° E., 43½ lks.  
dist., mkd. T58 R38E S20 NT.

A fir, 25 ins. diam., bears S. 69° W., 99 lks.  
dist., mkd. T58 R38E S19 NT.

A fir, 20 ins. diam., bears N. 64° W., 50 lks.  
dist., mkd. T58 R38E S18 NT.

Set a steel fence post alongside aluminum post.

Corner is located 50 lks. N. of abandoned dirt road, 15  
lks. wide, bears N. 75° W. and S. 75° E.

The ¼ sec. cor. of secs. 17 and 20, determined at record  
bearing and distance from the original bearing trees:

A ponderosa pine, 18 ins. diam., bears S. 74° W.,  
81 lks. dist., with scribe marks 4 & 5 visible on  
opened blaze.

A ponderosa pine, 48 ins. diam., bears N. 20° W.,  
55 lks. dist., with opened blaze, no marks  
visible.

At the corner point

UNION COUNTY  
SURVEYOR

Date received 2-2-84

Date filed 2-28-84

By G. LANGLITZ, DEPUTY

File No. 829-84R

PAGE 2/2