

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 38 E., Willamette Meridian, Oregon

CHAIN:

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 13 ins. in the ground, to solid rock, in a mound of stone, 3¼ ft. base, to top, with aluminum cap mkd.

T 5 S R 38 E

¼

S 29 | S 28

1982

from which a new bearing tree

A ponderosa pine, 10 ins. diam., bears S. 12° W., 66 lks. dist., mkd. ¼ S29 BT.

Deposit corner stone alongside aluminum post.

The cor. of secs. 20, 21, 28, and 29, determined at record bearing and distance from the remains of the original bearing trees:

A fir, 30 ins. diam., bears S. 45° E., 12 lks. dist., with healed blaze.

A pine stump, 28 ins. diam., bears S. 60° W., 17 lks. dist., with scribe marks S29 visible on partially healed blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, to solid rock, in a mound of stone, 3 ft. base, to top, with aluminum cap mkd.

T 5 S R 38 E

S 20 | S 21

S 29 | S 28

1982

from which new bearing trees

A ponderosa pine, 10 ins. diam., bears N. 26° E., 82¼ lks. dist., mkd. T5S R38E S21 BT.

A fir, 12 ins. diam., bears S. 23¼° W., 77 lks. dist., mkd. T5S R38E S29 BT.

A fir, 15 ins. diam., bears N. 67° W., 62¼ lks. dist., mkd. T5S R38E S20 BT.

Set a steel fence post alongside aluminum post.

The cor. of secs. 16, 17, 20, and 21, determined at record distance from the remains of the original bearing trees:

A ponderosa pine snag, 30 ins. diam., bears N. 47° E., 37 lks. dist., with scribe marks T5S R38E S16 BT visible on bark.

A ponderosa pine, 20 ins. diam., bears S. 35° W., 11 lks. dist., with healed blaze.

UNION COUNTY
SURVEYOR

Date Received 2-2-84

Date Filed 2-28-84

By G. LANGLITZ, DEPUTY

File No. 819-84R

FIELD NOTE PAPER

34

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 38 E., Willamette Meridian, Oregon

CHAINS

UNION COUNTY
SURVEYOR

Date Received 2-2-84Date Filed 2-28-84By G. LANGLITZ DEPUTYFile No. 819-84 R

PAGE 3/3

A ponderosa pine snag, 10 ins. diam., bears
N. 30° W., 33 lks. dist., with scribe mark S
visible on opened blaze. (Record, N. 28° W.)

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 20
ins. in the ground, to solid rock, in a mound of stone,
3 ft. base, to top, with aluminum cap mkd.

T 5 S R 38 E
S 17 | S 16
S 20 | S 21
1982

from which new bearing trees

A ponderosa pine, 10 ins. diam., bears N. 45° E.,
59 lks. dist., mkd. T5S R38E S16 BT.

A ponderosa pine, 18 ins. diam., bears S. 84° E.,
38 lks. dist., mkd. T5S R38E S21 BT.

A ponderosa pine, 10 ins. diam., bears N. 10¼° W.,
31¼ lks. dist., mkd. T5S R38E S17 BT.

The cor. of secs. 8, 9, 16, and 17, monumented with the
original basalt stone, 14 x 12 x 6 ins., firmly set 9
ins. in the ground, no marks visible, from which the
remains of the original bearing trees:

A fir, 12 ins. diam., bears N. 27° E., 5 lks.
dist., with illegible scribe marks visible on
opened blaze.

A fir snag, 10 ins. diam., bears S. 22° E., 6 lks.
dist., with healed blaze.

A ponderosa pine snag, 12 ins. diam., bears
S. 50° W., 8 lks. dist., with scribe marks S17
BT visible on open blaze. (Record, 15 lks.)

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 22
ins. in the ground, in a collar of stone, with aluminum
cap mkd.

T 5 S R 38 E
S 8 | S 9
S 17 | S 16
1982

from which new bearing trees

A fir, 10 ins. diam., bears S. 49° E., 37¼ lks.
dist., mkd. T5S R38E S16 BT.

A fir, 11 ins. diam., bears S. 50° W., 123¼ lks.
dist., mkd. T5S R38E S17 BT.

A fir, 13 ins. diam., bears N. 29° W., 51 lks.
dist., mkd. T5S R38E S8 BT.

Deposit corner stone and set a steel fence post
alongside aluminum post.