

N-15

R623

Form 9600-9  
(December 1979)  
(Formerly 9100-6)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

23

# FIELD NOTES

OF THE

REMONUMENTATION OF CERTAIN ORIGINAL CORNER POINTS,

TOWNSHIP 5 SOUTH, RANGE 38 EAST,

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Of the WILLAMETTE Meridian,  
in the State of OREGON

### EXECUTED BY

Scott R. McIntyre, Cadastral Surveyor

Under special instructions dated July 13, 19 79, approved July 17, 1979

\_\_\_\_\_, which provided for the surveys included under U.S. Survey/Group  
Number 1000, and assignment instructions dated July 30, 19 82

Survey commenced AUGUST 20, 19 82

Survey completed AUGUST 31, 19 82

<b>UNION COUNTY SURVEYOR</b>	
Date Received	<u>2-2-84</u>
Date Filed	<u>2-28-84</u>
By	<u>G. LANGLITZ, DEPUTY</u>
File No.	<u>813-84 R</u>

Remonumentation of Certain Original Corner Points,  
T. 5 S., R. 38 E., Willamette Meridian, Oregon

CHAIN

A fir, 25 ins. diam., bears N. 37° W., 51 lks.  
dist., with healed blaze. (Record, N. 57° W.)

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 15  
ins. in the ground, to solid rock, in a mound of stone,  
3 ft. base, to top, with aluminum cap mkd.

T 5 S R 38 E  
S 21 | S 22  
S 28 | S 27  
1982

from which new bearing trees

A fir, 6 ins. diam., bears N. 68° E., 29½ lks.  
dist., mkd. T58 R38E S27 BT.

A fir, 7 ins. diam., bears S. 47° E., 38 lks.  
dist., mkd. T58 R38E S27 BT.

A fir, 15 ins. diam., bears S. 26° W., 49 lks.  
dist., mkd. T58 R38E S28 BT.

Corner is located in a fence line, extending E. and W.

The ¼ sec. cor. of secs. 21 and 22, monumented with the  
original basalt stone, 16 x 10 x 4 ins., firmly set 10  
ins. in the ground, mkd. ¼ on W. face, from which the  
original bearing trees:

A fir, 22 ins. diam., bears N. 61½° E., 11 lks.  
dist., with healed blaze.

A fir, 20 ins. diam., bears N. 54½° W., 17 lks.  
dist., with healed blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 22  
ins. in the ground, in a collar of stone, with aluminum  
cap mkd.

T 5 S R 38 E  
¼  
S 21 | S 22  
1982

Deposit corner stone and set a steel fence post  
alongside aluminum post.

The ¼ sec. cor. of secs. 15 and 22, monumented with the  
original basalt stone, 12 x 10 x 6 ins., firmly set 7  
ins. in the ground, mkd. ¼ on N. face, from which the  
remains of the original bearing trees:

A decayed pine stump, size indeterminate, bears  
S. 19° W., 27 lks. dist., with scribe marks  
¼ S BT visible on open blaze.

A decayed fir snag, 15 ins. diam., bears N. 33° W.,  
9 lks. dist., with scribe marks ¼ S BT visible  
on open blaze.

UNION COUNTY  
SURVEYOR

Date Received 2-2-84

Date Filed 2-28-84

By G. LANGUTZ, DEPUTY

File No. 813-84 R

Remonumentation of Certain Original Corner Points,  
T. 5 S., R. 38 E., Willamette Meridian, Oregon

CHAINS

UNION COUNTY  
SURVEYOR

Date received 2-2-84Date filed 2-28-84By G. LANGLITZ, DEPUTYFile No. 813-84R

PAGE 3/3

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with aluminum cap mkd.

T 5 S R 38 E  
¼ S 15  
S 22  
1982

from which new bearing trees

A ponderosa pine, 5 ins. diam., bears S. 3° E., 56½ lks. dist., mkd. ¼ S22 BT.

A fir, 8 ins. diam., bears N. 22° W., 33 lks. dist., mkd. ¼ S15 BT.

Deposit corner stone and set a steel fence post alongside aluminum post.

The ¼ sec. cor. of secs. 10 and 15, monumented with the original basalt stone, 12 x 8 x 6 ins., firmly set 4 ins. in the ground, no marks visible, from which the remains of an original bearing tree:

A root hole, bears S. 48° W., 8 lks. dist., with a decayed larch alongside, size indeterminate, with illegible scribe marks visible.

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with aluminum cap mkd.

T 5 S R 38 E  
¼ S 10  
S 15  
1982

from which new bearing trees

A fir, 23 ins. diam., bears N. 17° E., 25 lks. dist., mkd. ¼ S10 BT.

A larch, 8 ins. diam., bears S. 30° E., 14 lks. dist., mkd. ¼ S15 BT.

Deposit corner stone and set a steel fence post alongside aluminum post.

The cor. of secs. 28, 29, 32, and 33, determined from the remains of the original bearing trees:

A larch, 25 ins. diam., bears S. 50° W., 26 lks. dist., with scribe marks 8 32 visible on open blaze. (Record, S. 55° W.)

A sawed pine stump, 45 ins. diam., bears N. 36° W., 67 lks. dist., no marks visible. (Record, N. 40° W.)

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground, to solid rock, in a mound of stone, ¾ st. base, to top, with aluminum cap mkd.