

R623

Form 9600-9
(December 1979)
(formerly 9100-6)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

23

FIELD NOTES
OF THE

REMONUMENTATION OF CERTAIN ORIGINAL CORNER POINTS,

TOWNSHIP 5 SOUTH, RANGE 38 EAST,

[Lined area for field notes]

Of the WILLAMETTE Meridian,
in the State of OREGON

EXECUTED BY

Scott R. McIntyre, Cadastral Surveyor

Under special instructions dated July 13, 19 79, approved July 17, 1979

which provided for the surveys included under U.S. Survey/Group
Number 1000, and assignment instructions dated July 30, 19 82

Survey commenced August 20, 19 82
Survey completed August 31, 19 82

UNION COUNTY
SURVEYOR

Date Received 2-2-84

Date Filed 2-28-84

By G. LANGLITZ, DEPUTY

File No. 808-84 R

Re monumentation of Certain Original Corner Points,
T. 5 S., R. 38 E., Willamette Meridian, Oregon

	<p>from which new bearing trees</p> <p>A larch, 17 ins. diam., bears N. 64° E., 17 lks. dist., mhd. T58 R38E S12 BT.</p> <p>A fir, 8 ins. diam., bears S. 22° E., 32 lks. dist., mhd. T58 R38E S13 BT.</p> <p>A fir, 8 ins. diam., bears S. 25° W., 21½ lks. dist., mhd. T58 R38E S14 BT.</p> <p>A fir, 8 ins. diam., bears N. 44° W., 27 lks. dist., mhd. T58 R38E S11 BT.</p> <p>Set a steel fence post alongside aluminum post.</p>
<p>UNION COUNTY SURVEYOR</p> <p>Date Received <u>2-2-84</u></p> <p>Date Filed <u>2-28-84</u></p> <p>By <u>G. LANGLITZ, DEPUTY</u></p> <p>File No. <u>808-84 R</u></p>	<p>The ¼ sec. cor. of secs. 14 and 23, monumented with the original basalt stone, 12 x 12 x 5 ins., firmly set 8 ins. in the ground, no marks visible, from which the remains of the original bearing trees:</p> <p>A fir, 13 ins. diam., bears N. 62° E., 23 lks. dist., with illegible scribe marks visible on opened base.</p> <p>A decayed fir stump, 12 ins. diam., bears S. 65° E., 30 lks. dist., with weathered base, no marks visible.</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, in a collar of stone, with aluminum cap mhd.</p> <p style="text-align: center;">T 5 S R 38 E ¼ S 14 ¼ S 23 1982</p>
<p>PAGE 2/2</p>	<p>from which a new bearing tree</p> <p>A fir, 10 ins. diam., bears S. 60° E., 15 lks. dist., mhd. ¼ S23 BT.</p> <p>Deposit corner stone and set a steel fence post alongside aluminum post.</p>
	<p>The ¼ sec. cor. of secs. 10 and 11, monumented with the original basalt stone, 16 x 14 x 6 ins., supported by a mound of stone, 3 ft. base, 2 ft. high, from which the original bearing trees:</p> <p>A fir, 29 ins. diam., bears S. 55° E., 36 lks. dist., with scribe marks ¼ S visible on partially opened base.</p> <p>A larch stump, 9 ins. diam., bears S. 40° W., 15 lks. dist., with a down larch alongside, with opened base, no marks visible. (Record, S. 44° W.)</p> <p>At the corner point</p>