

P-5

R623

Form 9400-9
(December 1979)
(Formerly 9180-6)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL.

23

FIELD NOTES
OF THE

REMONUMENTATION OF CERTAIN ORIGINAL CORNER POINTS,

TOWNSHIP 5 SOUTH, RANGE 38 EAST,

Of the WILLAMETTE Meridian,
In the State of OREGON

EXECUTED BY

Scott R. McIntyre, Cadastral Surveyor

Under special instructions dated July 13, 1979, approved July 17, 1979.

, which provided for the surveys included under U.S. Survey Group
Number 1000, and assignment instructions dated July 30, 1982.

Survey commenced August 20, 1982
Survey completed August 31, 1982

**UNION COUNTY
SURVEYOR**

Date Received 2-2-84

Date Filed 2-28-84

By G. LANGLITZ, DEPUTY

File No. 828-84 R

38

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 38 E., Willamette Meridian, Oregon

T 5 S R 38 E
S 19 | S 20

S 30 | S 29
1982

from which new bearing trees

A fir, 9 ins. diam., bears N. 3° E., 45 lks.
dist., mkd. T5S R38E 820 BT.

A fir, 13 ins. diam., bears S. 73° W., 27 lks.
dist., mkd. T5S R38E 830 BT.

A fir, 8 ins. diam., bears N. 55½° W., 29½ lks.
dist., mkd. T5S R38E 819 BT.

Set a steel fence post alongside aluminum post.

The ¼ sec. cor. of secs. 19 and 30, determined at record
bearing and distance, from the remains of the original
bearing trees:

A ponderosa pine, 28 ins. diam., bears N. 70° E.,
30 lks. dist., with healed blaze.

A ponderosa pine snag, 28 ins. diam., bears
S. 87° W., 56 lks. dist., with scribe marks
4 S visible on opened blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 15
ins. in the ground, to solid rock, in a mound of stone,
2½ ft. base, to top, with aluminum cap mkd.

T 5 S R 38 E
4 S 19

S 30
1982

from which a new bearing tree

A ponderosa pine, 12 ins. diam., bears S. 10° E.,
69 lks. dist., mkd. 4 S 30 BT.

Set a steel fence post alongside aluminum post.

The ¼ sec. cor. of secs. 19 and 20, monumented with the
original basalt stone, 12 x 10 x 6 ins., loosely set 5
ins. in the ground, no marks visible, from which the
remains of the original bearing trees:

A fir, 14 ins. diam., bears East, 22 lks. dist.,
with scribe marks BT visible on opened blaze.

A saved fir stump, 23 ins. diam., bears N. 56° W.,
50 lks. dist., no marks visible. (Record,
N. 52° W.)

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 21
ins. in the ground, in a collar of stone, with aluminum
cap mkd.

T 5 S R 38 E
4 S 19 | S 20

S 30 | S 29
1982

UNION COUNTY
SURVEYOR

Date Received 2-2-84

Date Filed 2-28-84

By G. LANGRITZ, Deputy

File No. 828-84 R

PAGE 2 / 3

UNION COUNTY SURVEYOR	
Date received	<u>2-28-84</u> CHAINS
Date filed	<u>2-28-84</u>
By	<u>G. LANGLITZ, Deputy</u>
File No.	<u>828-84 R</u>

PAGE 3/3

15

39

Renumeration of Certain Original Corner Points,
T. 5 S., R. 38 E., Willamette Meridian, Oregon

from which a new bearing tree

A ponderosa pine, 13 ins. diam., bears N. $84\frac{1}{2}$ ° W.,
69 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S19 BT.

Deposit corner stone and set a steel fence post
alongside aluminum post.

The cor. of secs. 17, 18, 19, and 20, determined at record
bearing and distance from which the remains of the orig-
inal bearing trees:

A root hole, bears N. 50° E., 68 lks. dist., with
a down pine alongside, 24 ins. diam., with scribe
marks T5S R38E S17 BT visible on open blaze.

A root hole, bears S. 64° E., 50 lks. dist., with
a down and decayed pine alongside, size indeter-
minate, no marks visible.

A root hole, bears N. 47° W., 43 lks. dist.

At the corner point

Set an aluminum post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 15
ins. in the ground, to solid rock, in a mound of stone,
 $3\frac{1}{2}$ ft. base, to top, with aluminum cap mkd.

T 5 S R 38 E
S 18 S 17
S 19 3 20
1982

from which new bearing trees

A fir, 11 ins. diam., bears N. 69° E., 78 lks.
dist., mkd. T5S R38E S17 BT.

A fir, 20 ins. diam., bears S. 82° E., 43 $\frac{1}{2}$ lks.
dist., mkd. T5S R38E S20 BT.

A fir, 25 ins. diam., bears S. 69° W., 99 lks.
dist., mkd. T5S R38E S19 BT.

A fir, 20 ins. diam., bears N. 64° W., 50 lks.
dist., mkd. T5S R38E S18 BT.

Set a steel fence post alongside aluminum post.

Corner is located 50 lks. N. of abandoned dirt road, 15
lks. wide, bears N. 75° W. and S. 75° E.

The $\frac{1}{4}$ sec. cor. of secs. 17 and 20, determined at record
bearing and distance from the original bearing trees:

A ponderosa pine, 18 ins. diam., bears S. 74° W.,
81 lks. dist., with scribe marks 4 S visible on
opened blaze.

A ponderosa pine, 48 ins. diam., bears N. 20° W.,
55 lks. dist., with opened blaze, no marks
visible.

At the corner point