

R-3

R623

**Form 9600-9  
(December 1979)**  
**(Formerly 9180-6)**

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL.

23

# FIELD NOTES

**REMONUMENTATION OF CERTAIN ORIGINAL CORNER POINTS,**

**TOWNSHIP 5 SOUTH, RANGE 38 EAST.**

Of the WILLAMETTE Meridian,  
in the State of OREGON

**EXECUTED BY**

**Scott R. McIntyre, Cadastral Surveyor**

Under special instructions dated July 13, 1979, approved July 17, 1979

\_\_\_\_\_ which provided for the surveys included under U.S. Survey/Group  
Number 1000, and assignment instructions dated July 30 1982

Survey commenced August 20, 1982

# **UNION COUNTY SURVEYOR**

Date Received 2-2-84

Date Filed 2-28-84

By G. LANGUET Deputy

File No. 827-84 R

~~Remonumentation of Certain Original Corner Points,  
T. 5 S., R. 38 E., Willamette Meridian, Oregon~~

T 5 S R 38 E  
S 19 | S 20  
S 30 | S 29  
1982

~~from which new bearing trees~~

~~A fir, 9 ins. diam., bears N. 3° E., 45 lks.  
dist., mkd. T5S R38E S20 ST.~~

~~A fir, 13 ins. diam., bears S. 73° W., 27 lks.  
dist., mkd. T5S R38E S30 ST.~~

~~A fir, 8 ins. diam., bears N. 35½° W., 29½ lks.  
dist., mkd. T5S R38E S19 ST.~~

~~Set a steel fence post alongside aluminum post.~~

The  $\frac{1}{4}$  sec. cor. of secs. 19 and 30, determined at record bearing and distance, from the remains of the original bearing trees:

~~A ponderosa pine, 28 ins. diam., bears N. 70° E.,  
30 lks. dist., with healed blemish.~~

~~A ponderosa pine snag, 28 ins. diam., bears  
S. 87° W., 56 lks. dist., with scribe marks  
 $\frac{1}{4}$  S visible on opened blemish.~~

~~At the corner point~~

~~Set an aluminum post, 28 ins. long,  $2\frac{1}{4}$  ins. diam., 15  
ins. in the ground, to solid rock, in a mound of stone,  
 $2\frac{1}{4}$  ft. base, to top, with aluminum cap mkd.~~

T 5 S R 38 E  
S 19  
S 30  
1982

~~from which a new bearing tree~~

~~A ponderosa pine, 12 ins. diam., bears S. 10° E.,  
69 lks. dist., mkd.  $\frac{1}{4}$  S30 ST.~~

~~Set a steel fence post alongside aluminum post.~~

The  $\frac{1}{4}$  sec. cor. of secs. 19 and 20, monumented with the  
original basalt stone, 12 x 10 x 6 ins., loosely set 5  
ins. in the ground, no marks visible, from which the  
remains of the original bearing trees:

~~A fir, 14 ins. diam., bears East, 22 lks. dist.  
with scribe marks ST visible on opened blemish.~~

~~A sawed fir stump, 23 ins. diam., bears N. 56° W.,  
50 lks. dist., no marks visible. (Record,  
N. 52° W.)~~

~~At the corner point~~

~~Set an aluminum post, 28 ins. long,  $2\frac{1}{4}$  ins. diam., 21  
ins. in the ground, in a pillar of stone, with aluminum  
cap mkd.~~

T 5 S R 38 E  
S 19 | S 20  
1982