

R-5

R623

Form 9600-9
(December 1979)
(formerly 9188-6)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL.

23

FIELD NOTES

OF THE

REMONUMENTATION OF CERTAIN ORIGINAL CORNER POINTS,

TOWNSHIP 5 SOUTH, RANGE 38 EAST,

[Empty lined area for field notes]

Of the WILLAMETTE Meridian,
in the State of OREGON

EXECUTED BY

Scott R. McIntyre, Cadastral Surveyor

Under special instructions dated July 13, 19 79, approved July 17, 1979

which provided for the surveys included under U.S. Survey/Group
Number 1000, and assignment instructions dated July 30, 19 82

Survey commenced August 20, 19 82

Survey completed August 31, 19 82

**UNION COUNTY
SURVEYOR**

Date Received 2-2-84

Date Filed 2-28-84

By G. LANGLITZ, DEPUTY

File No. 826-84R

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 38 E., Willamette Meridian, Oregon

CHALERS

Set an aluminum post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, in a collar of stone, with aluminum cap mkd.

T 5 S R 38 E
¼ S 30
¼ S 31
1982

from which new bearing trees

A larch, 12 ins. diam., bears N. 38° E., 11 lks. dist., mkd. ¼ S30 BT.

A fir, 7 ins. diam., bears S. 32½° E., 8 lks. dist., mkd. ¼ S31 BT.

Deposit corner stone and set a steel fence post alongside aluminum post.

The ¼ sec. cor. of secs. 29 and 30, determined at record bearing and distance from the remains of an original bearing tree:

A ponderosa pine snag, 17 ins. diam., bears S. 72° W., 31 lks. dist., with scribe marks ¼ S BT visible on open blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, to solid rock, in a mound of stone, 3 ft. base, to top, with aluminum cap mkd.

T 5 S R 38 E
¼ S 30 | S 29
1982

from which new bearing trees

A fir, 17 ins. diam., bears N. 66° E., 70½ lks. dist., mkd. ¼ S29 BT.

A fir, 15 ins. diam., bears S. 44° W., 45½ lks. dist., mkd. ¼ S30 BT.

Set a steel fence post alongside aluminum post.

The cor. of secs. 19, 20, 29, and 30, determined at record bearing and distance, from the remains of the original bearing trees:

A fir, 22 ins. diam., bears S. 33° E., 42 lks. dist., with scribe marks S29 visible on decayed and open blaze.

A larch snag, 13 ins. diam., bears N. 25° W., 24 lks. dist., with scribe marks S19 visible on opened blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, in a collar of stone, with aluminum cap mkd.

UNION COUNTY
SURVEYOR

Date received 2-2-84

Date filed 2-28-84

By G. LANGLITZ, DEPUTY

File no. 826-84R

PAGE 2/3

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 38 E., Willamette Meridian, Oregon

CHAIN

T 5 S R 38 E
S 19 | S 20
S 30 | S 29
1982

UNION COUNTY
SURVEYOR

Date Received 2-2-84Date Filed 2-28-84By G. LANGLITZ, DEPUTYFile No. 826-84R

from which new bearing trees

A fir, 9 ins. diam., bears N. 3° E., 45 lks.
dist., mkd. T5S R38E S20 BT.

A fir, 13 ins. diam., bears S. 73° W., 27 lks.
dist., mkd. T5S R38E S30 BT.

A fir, 8 ins. diam., bears N. 35½° W., 29½ lks.
dist., mkd. T5S R38E S19 BT.

Set a steel fence post alongside aluminum post.

PAGE 3/3

The ¼ sec. cor. of secs. 19 and 30, determined at record
bearing and distance, from the remains of the original
bearing trees:

A ponderosa pine, 28 ins. diam., bears N. 70° E.,
30 lks. dist., with healed blaze.

A ponderosa pine snag, 28 ins. diam., bears
S. 87° W., 56 lks. dist., with scribe marks
¼ S visible on opened blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 15
ins. in the ground, to solid rock, in a mound of stone,
2½ ft. base, to top, with aluminum cap mkd.

T 5 S R 38 E
¼ S 19
S 30
1982

from which a new bearing tree

A ponderosa pine, 12 ins. diam., bears S. 10° E.,
69 lks. dist., mkd. ¼ S30 BT.

Set a steel fence post alongside aluminum post.

The ¼ sec. cor. of secs. 19 and 20, monumented with the
original basalt stone, 12 x 10 x 6 ins., loosely set 5
ins. in the ground, no marks visible, from which the
remains of the original bearing trees:

A fir, 14 ins. diam., bears East, 22 lks. dist.,
with scribe marks BT visible on opened blaze.

A saved fir stump, 23 ins. diam., bears N. 56° W.,
50 lks. dist., no marks visible. (Record,
N. 52° W.)

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 21
ins. in the ground, in a collar of stone, with aluminum
cap mkd.

T 5 S R 38 E
¼ S 19 | S 20
S 30
1982