


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

This $\frac{1}{4}$ corner was set by deputy surveyor W.B. Barr, under Contract No. 388, dated May 7, 1881. He states he set a marked basalt rock 16" x 10" x 4" for $\frac{1}{4}$ sec. cor. from which:
 A pine 10" dia. bears South, 9 lks. dist.
 A pine 5" dia. bears N 60 E, 8 lks. dist.



Description of corner evidence found:

At the assumed $\frac{1}{4}$ corner location I made an extensive search and found no trace of the original corner. There has been extensive logging activity in this area on several occasions during the past 80 years or more. All evidence of the corner appears to have been destroyed.

Description of monument and accessories I established to perpetuate the original location of this corner:

With no trace of evidence found I established this $\frac{1}{4}$ corner by single proportioning. I then set an Alum. cap on a 2" x 30" pipe, with a magnet fixed in the cap, at the corner location. I buried the pipe to within 6" above the surface of the ground. I then placed a mound of stone $3\frac{1}{2}$ feet dia. and 1 foot high covering the monument. From which I set two new bearing trees:
 A pine 9" dia. bears N 15 13 W, 33.00 feet and scribed $\frac{1}{4}$ S S 23 BT.
 A douglas fir 7" dia. bears S 07 37 E, 30.12 feet and scribed $\frac{1}{4}$ S S 26 BT.

UNION COUNTY SURVEYOR
Date Received <u>9-22-87</u>
Date Filed <u>9-25-87</u>
By <u>G. LANGLITZ, DEPUTY</u>
File No. <u>120-87R</u>

REGISTERED PROFESSIONAL LAND SURVEYOR
<i>James H. Hambleton</i>
<u>9-25-87</u>
OREGON JULY 10, 1964 JAMES H. HAMBLETON 645

REFER TO SURVEY 28-87

Office of..... County of.....
 State of....., I hereby certify that the within instrument was filed in this office
 for record on the..... day of....., 19.....
 by
 (COUNTY OFFICIAL) (DEPUTY)