

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 38 E., Willamette Meridian, Oregon

CHAINS

Set an aluminum post, 28 ins. long, 2 1/4 ins. diam., 23 ins. in the ground, in a collar of stone, with aluminum cap mkd.

T 5 S R 38 E
1/4 S 30
1/4 S 31
1982

from which new bearing trees

A larch, 12 ins. diam., bears W. 38° E., 11 lks. dist., mkd. 1/4 S30 BT.

A fir, 7 ins. diam., bears S. 32 1/2° E., 8 lks. dist., mkd. 1/4 S31 BT.

Deposit corner stone and set a steel fence post alongside aluminum post.

The 1/4 sec. cor. of secs. 29 and 30, determined at record bearing and distance from the remains of an original bearing tree:

A ponderosa pine snag, 17 ins. diam., bears S. 72° W., 31 lks. dist., with scribe marks 1/4 S BT visible on open blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2 1/4 ins. diam., 18 ins. in the ground, to solid rock, in a mound of stone, 3 ft. base, to top, with aluminum cap mkd.

T 5 S R 38 E
1/4 S 30 | S 29
1982

from which new bearing trees

A fir, 17 ins. diam., bears W. 66° E., 78 1/2 lks. dist., mkd. 1/4 S29 BT.

A fir, 15 ins. diam., bears S. 44° W., 45 1/2 lks. dist., mkd. 1/4 S30 BT.

Set a steel fence post alongside aluminum post.

The cor. of secs. 19, 20, 29, and 30, determined at record bearing and distance, from the remains of the original bearing trees:

A fir, 22 ins. diam., bears S. 33° E., 42 lks. dist., with scribe marks S29 visible on decayed and open blaze.

A larch snag, 13 ins. diam., bears N. 25° W., 24 lks. dist., with scribe marks S19 visible on opened blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2 1/4 ins. diam., 23 ins. in the ground, in a collar of stone, with aluminum cap mkd.

UNION COUNTY SURVEYOR	
Date received	<u>2-2-84</u>
Date filed	<u>2-28-84</u>
By	<u>G. LANGLITZ DEPUTY</u>
File no.	<u>825-84 R</u>

PAGE 2/2