

T-9

R623

Form 9600-9
(December 1979)
(formerly 9188-6)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL.

23

FIELD NOTES
OF THE

REMONUMENTATION OF CERTAIN ORIGINAL CORNER POINTS,

TOWNSHIP 5 SOUTH, RANGE 38 EAST,

[Lined area for field notes]

Of the WILLAMETTE Meridian,
in the State of OREGON

EXECUTED BY

Scott R. McIntyre, Cadastral Surveyor

Under special instructions dated July 13, 19 79, approved July 17, 1979

which provided for the surveys included under U.S. Survey/Group
Number 1000, and assignment instructions dated July 30, 19 82

Survey commenced August 20, 19 82

Survey completed August 31, 19 82

UNION COUNTY
SURVEYOR

Date Received 2-2-84

Date Filed 2-28-84

By G. LANGLITZ, DEPUTY

File No. 817-84 R

Page 1/3

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 38 E., Willamette Meridian, Oregon

CHAINS

T 5 S R 38 E
S 29 | S 28
S 32 | S 33
1982

from which new bearing trees

A fir, 11 ins. diam., bears N. 88° E., 132½ lks.
dist., mkd. T5S R38E S28 BT.

A fir, 10 ins. diam., bears S. 44° E., 85 lks.
dist., mkd. T5S R38E S33 BT.

A larch, 13 ins. diam., bears W. 18° W., 69 lks.
dist., mkd. T5S R38E S29 BT.

Set a steel fence post alongside aluminum post.

Corner is located on W. edge of logging road, 20 lks.
wide, bears N. and S.

The ¼ sec. cor. of secs. 28 and 33, determined at record
bearing and distance from the remains of the original
bearing trees:

A pine snag, 36 ins. diam., bears S. 20° E., 18
lks. dist., with scribe marks ¼ S BT visible on
open blaze.

A sawed pine stump, 36 ins. diam., bears N. 75° W.,
57 lks. dist., no marks visible.

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 21
ins. in the ground, in a collar of stone, with aluminum
cap mkd.

T 5 S R 38 E
¼ S 28
¼ S 33
1982

from which new bearing trees

A ponderosa pine, 13 ins. diam., bears S. 24° E.,
37 lks. dist., mkd. ¼ S33 BT.

A fir, 28 ins. diam., bears N. 66° W., 31½ lks.
dist., mkd. ¼ S28 BT.

Corner is located in a fence line, extending N. and S.

The ¼ sec. cor. of secs. 28 and 29, monumented with the
original basalt stone, 16 x 12 x 4 ins., firmly set 10
ins. in the ground, no marks visible, from which the
remains of the original bearing trees:

A ponderosa pine, 21 ins. diam., bears N. 89° E.,
158 lks. dist., with healed blaze. (Record,
165 lks.)

A sawed pine stump, 40 ins. diam., bears S. 104° W.,
244 lks. dist., no marks visible.

UNION COUNTY
SURVEYOR

Date Received 2-2-84

Date Filed 2-28-84

By G. LANGLITZ, DEPUTY

File No. 817-84R

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 38 E., Willamette Meridian, Oregon

CHAIN#

UNION COUNTY
SURVEYOR

Date Received 2-2-84

Date Filed 2-28-84

By G. LANGLITZ DEPUTY

File No. 817-84 R

PAGE 3/3

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 13 ins. in the ground, to solid rock, in a mound of stone, 3½ ft. base, to top, with aluminum cap mkd.

T 5 S R 38 E
S 29 | S 28
1982

from which a new bearing tree

A ponderosa pine, 10 ins. diam., bears S. 12° W., 66 lks. dist., mkd. ¼ S29 BT.

Deposit corner stone alongside aluminum post.

The cor. of secs. 20, 21, 28, and 29, determined at record bearing and distance from the remains of the original bearing trees:

A fir, 30 ins. diam., bears S. 45° E., 12 lks. dist., with healed blaze.

A pine stump, 28 ins. diam., bears S. 60° W., 17 lks. dist., with scribe marks S29 visible on partially healed blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, to solid rock, in a mound of stone, 3 ft. base, to top, with aluminum cap mkd.

T 5 S R 38 E
S 20 | S 21
S 29 | S 28
1982

from which new bearing trees

A ponderosa pine, 10 ins. diam., bears N. 26° E., 82½ lks. dist., mkd. T5S R38E S21 BT.

A fir, 12 ins. diam., bears S. 23½° W., 77 lks. dist., mkd. T5S R38E S29 BT.

A fir, 15 ins. diam., bears N. 67° W., 62½ lks. dist., mkd. T5S R38E S20 BT.

Set a steel fence post alongside aluminum post.

The cor. of secs. 16, 17, 20, and 21, determined at record distance from the remains of the original bearing trees:

A ponderosa pine snag, 30 ins. diam., bears N. 47° E., 37 lks. dist., with scribe marks T5S R38E S16 BT visible on bark.

A ponderosa pine, 20 ins. diam., bears S. 35° W., 11 lks. dist., with healed blaze.