

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


History of original corner establishment:

Original survey by W.B. Barr under Contract No. 388, dated May 7, 1881.

Marked a basalt rock, 14"x12"x6" for 1/4 sec. corner, from which:

- A Pine 30 in. diam. bears N 10°E 45 lks. dist.
- A Pine 28 in. diam. bears N 63°W 40 lks. dist.

T-17



Description of corner evidence found:

Found the original corner monument, a basalt stone, 14"x11"x6", loosely set, 5" in the ground, with chisel markings "1/4" on west face, from which:

A badly decayed Ponderosa Pine stump, approx. 30" dia. when cut, no markings found, bears N 63°W 26.4 feet to the approx. original face.

The position for the original NE bearing tree falls along a logging skid trail. We find fragments of roots and wood in the ground at its approx. location.

Description of monument and accessories I established to perpetuate the original location of this corner:

At the position of the found stone, we set a 2"x30" galvanized iron pipe, 24" in the ground, with brass cap attached, marked:

T5S R38E
1/4
S27 | S26
PLS 1099
1984

The original stone is buried along the east side of the brass-capped pipe.

We mark the following bearing trees:

- An 8" Ponderosa Pine, scribed "1/4 S 27 BT" on a double blaze bears S 81°W 32.4 ft.
- A 12" Douglas Fir, scribed "1/4 S 26 BT" on a double blaze bears N 43°E 7.8 ft.

Attached brass washer marked "LS 1099" to lower blaze of new BT's.
Magnetic Compass (Declination 20° East)
Steel Tape

September 20, 1984

Witnesses:

Gary Langlitz, LS 1099
Doug Wright

**UNION COUNTY
SURVEYOR**


Date Received 11-13-84

Date Filed 11-13-84

By G. LANGLITZ, DEPUTY

File No. 1027-84R

Office of



..... County of

State of, I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 19.....

..... by

(COUNTY OFFICIAL) (DEPUTY)