

V-3

R623

Form 9600-9  
(December 1979)  
(formerly 9180-6)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

23

**FIELD NOTES**  
OF THE

REMONUMENTATION OF CERTAIN ORIGINAL CORNER POINTS,

TOWNSHIP 5 SOUTH, RANGE 38 EAST,

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Of the WILLAMETTE Meridian,

In the State of OREGON

**EXECUTED BY**

Scott R. McIntyre, Cadastral Surveyor

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Under special instructions dated July 13, 19 79, approved July 17, 1979

\_\_\_\_\_, which provided for the surveys included under U.S. Survey/Group  
Number 1000, and assignment instructions dated July 30, 19 82

Survey commenced August 20, 19 82  
Survey completed August 31, 19 82

**UNION COUNTY  
SURVEYOR**

Date Received 2-2-84  
Date Filed 2-28-84  
By G. LANGLITZ, DEPUTY  
File No. 824-84R

Monumentation of Certain Original Corner Points,  
T. 5 S., R. 38 E., Willamette Meridian, Oregon

Deposit corner stone and set a steel fence post  
alongside aluminum post.

The cor. of secs. 29, 30, 31, and 32, monumented with the  
original basalt stone, 10 x 8 x 8 ins., firmly set 5 ins.  
in the ground, no marks visible, from which the remains  
of the original bearing trees:

A fir stump, 10 ins. diam., bears N. 54° E., 18  
lks. dist., with a down fir alongside, size  
indeterminate, with scribe marks T58 29 visible  
on open blaze. (Record, N. 59° E.)

A root hole, bears S. 32½° E., 17 lks. dist., with  
a down fir alongside, 5 ins. diam., with scribe  
marks S32 BT visible on open blaze.

A root hole, bears S. 8° W., 23 lks. dist., with  
a down larch alongside, 10 ins. diam., with  
scribe marks S31 BT visible on open blaze.

A root hole, bears N. 65° W., 17 lks. dist., with  
a down larch alongside, 15 ins. diam., with  
scribe marks S30 BT visible on open blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 23  
ins. in the ground, in a collar of stone, with aluminum  
cap mkd.

T 5 S R 38 E  
S 30 | S 29  
S 31 | S 32  
1982

from which new bearing trees

A lodgepole pine, 5 ins. diam., bears N. 19° E.,  
34 lks. dist., mkd. T58 R38E S29 BT.

A fir, 22 ins. diam., bears S. 68° E., 19 lks.  
dist., mkd. T58 R38E S32 BT.

A fir, 10 ins. diam., bears S. 36° W., 21 lks.  
dist., mkd. T58 R38E S31 BT.

A fir, 11 ins. diam., bears N. 73° W., 30 lks.  
dist., mkd. T58 R38E S30 BT.

Deposit corner stone and set a steel fence post  
alongside aluminum post.

The ¼ sec. cor. of secs. 30 and 31, monumented with the  
original basalt stone, 16 x 6 x 5 ins., firmly set 12  
ins. in the ground, in a collar of stone, no marks  
visible, from which the remains of an original bearing  
tree:

A sawed larch stump, 16 ins. diam., bears S. 70° W.,  
68 lks. dist., with a down larch snag alongside,  
size indeterminate, with scribe marks ¼ S BT  
visible on open blaze. (Record, 73 lks.)

At the corner point

UNION COUNTY  
SURVEYOR

Date Received 2-2-84

Date Filed 2-28-84

by G. LANGLITZ, DEPUTY

File No. 824-84 R

Remonumentation of Certain Original Corner Points,  
T. 5 S., R. 38 E., Willamette Meridian, Oregon

CHAINS

Set an aluminum post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, in a collar of stone, with aluminum cap mkd.

T 5 S R 38 E

$$\frac{1}{4} \begin{array}{l} S 30 \\ S 31 \end{array}$$

1982

from which new bearing trees

A larch, 12 ins. diam., bears N. 38° E., 11 lks. dist., mkd. ¼ S30 BT.

A fir, 7 ins. diam., bears S. 32½° E., 8 lks. dist., mkd. ¼ S31 BT.

Deposit corner stone and set a steel fence post alongside aluminum post.

UNION COUNTY  
SURVEYOR

Date Received 2-2-84Date filed 2-28-84By G. LANGLITZ, DEPUTYFile No. 824-84 R

PAGE 3/3

The ¼ sec. cor. of secs. 29 and 30, determined at record bearing and distance from the remains of an original bearing tree:

A ponderosa pine snag, 17 ins. diam., bears S. 72° W., 31 lks. dist., with scribe marks ¼ S BT visible on open blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, to solid rock, in a mound of stone, 3 ft. base, to top, with aluminum cap mkd.

T 5 S R 38 E

$$\frac{1}{4} \begin{array}{l} S 30 \\ S 29 \end{array}$$

1982

from which new bearing trees

A fir, 17 ins. diam., bears N. 66° E., 78½ lks. dist., mkd. ¼ S29 BT.

A fir, 15 ins. diam., bears S. 44° W., 45½ lks. dist., mkd. ¼ S30 BT.

Set a steel fence post alongside aluminum post.

The cor. of secs. 19, 20, 29, and 30, determined at record bearing and distance, from the remains of the original bearing trees:

A fir, 22 ins. diam., bears S. 33° E., 42 lks. dist., with scribe marks S29 visible on decayed and open blaze.

A larch snag, 13 ins. diam., bears N. 25° W., 24 lks. dist., with scribe marks S19 visible on opened blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, in a collar of stone, with aluminum cap mkd.

**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

**History of original corner establishment:**

Original corner set by William B. Barr, under GLO Contract No. 388, approved December 31, 1881.

Record States: Marked basalt rock 16x8x5 for ¼ sec corner, from which:

- Tamarack, 12 in diam., bears N 20° E, 40 lks dist.
- Tamarack, 12 in diam., bears S 70° W, 73 lks dist.

**Subsequent Monumentation**


Corner was remonumented by Scott R. McIntyre, under BLM Group No. 1000, approved December 27, 1983.

The ¼ sec. cor. of secs. 30 and 31, monumented with the original basalt stone, 16x6x5 ins., firmly set 12 ins. in the ground, in a collar of stone, no marks visible, from which the remains of an original bearing tree:

- A sawed larch stump, 16 ins. diam., bears S. 70° W., 68 lks. dist., with a down larch snag alongside, size indeterminate, with scribe marks ¼ S BT visible on open blaze.  
(Record, 73 lks.)

At the corner point: Set an aluminum post, 28 ins. long, 2 ½ ins. diam., 23 ins. in the ground, in a collar of stone, with aluminum cap mkd. (as shown below) from which new bearing trees:

- A larch, 12 ins. diam., bears N. 38° E., 11 lks. dist., mkd. 1/4 S30 BT.
- A fir, 7 ins. diam., bears S. 32 ½ ° E., 8 lks. dist., mkd. 1/4 S31 BT




**Description of corner evidence found:**

Found 2½ ins. diam. alum. pipe, projecting 5 ins. above ground, with rock collar, and standard BLM 3¼ ins. diam. alum. cap, marked as shown (Note: "2" is missing from date on cap):

From the recovered monument I find the original bearing tree remains:

- A sawed larch stump, 16 ins. diam., bears S. 70° W., 68 lks. dist. rotting with no visible scribing. And accessories mkd. by McIntyre:
- A larch, 14 ins. diam., bears N. 38° E., 11 lks. dist., alive and healthy, with healed blaze and Location Tag (54-5) attached.
- A white fir, 10 ins. diam., bears S. 32½° E., 8 lks. dist., alive and healthy, with healed blaze and Location Tag (54-5) attached.

Found guard post ±1.5 ft. S'ly.



**Description of monument and accessories I established to perpetuate original location of this corner:**

New bearing trees:

- A white fir, 9 ins. diam., bears S. 71½ ° W., 22.9 ft. dist., mkd. 1/4 S31 BT.
- A white fir, 6 ins. diam., bears N. 74° W., 26.2 ft. dist., mkd. 1/4 S30 BT.

All new bearing trees are marked on a single blaze and have a nail with a brass washer stamped "LS 2648" right side center for distance measurements.

Painted 6 ins. red bands and added Bearing Tree (54-3) and Land Survey Monument (54-9) signs as needed to all bearing trees.

Auto C/A geographic position:

- Lat. 45°05'35.9" N
- Long. 118°06'22.3" W

I hereby certify that the corner is monumented and accessories taken as described, using a Warren Knight staff compass, set with 15° East declination, and steel tape on June 19, 2014.

Witnesses: Brenda Johnson and Jon Howells

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

**Deceased**

OREGON  
JANUARY 18, 1994  
RON C. WALTER  
2648

Renewal Date: June 30, 2016

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Will R. Wells*

OREGON  
July 22, 1977  
WILLIAM R. WELLS  
1106

Renewal Date: June 30, 2016

**UNION COUNTY  
SURVEYOR**

---

Date Received 2/25/15

Date Filed 2/25/15

By *Phil G. Johnson*

File No. 034-2015R

**NOTE:** See "Explanation for Successor Certifying Surveyor" statement in Narrative of Record of Survey, CS 010-2015, filed concurrently with this Land Corner Record.