


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

V-15

History of original corner establishment:

Original survey by W.B. Barr under Contract No. 388, dated May 7, 1881.
Marked a basalt stone, 16"x12"x6" for 1/4 Sec. corner, from which:
A Pine 40 in. diam. bears S 20°W 44 lks. dist.
A Pine 30 in. diam. bears N 23°E 64 lks. dist.



Description of corner evidence found:

At the corner position, we find a 16"x12"x6" basalt stone, loosely set, with chisel markings "1/4" visible on the north face, from which the remains of the original bearing trees:

- A Ponderosa Pine Stump, badly decayed, size indeterminate, with fragments of scribed wood alongside, bears S 25°W 29.0 feet,
- And a Ponderosa Pine Stump, approximately 38" diameter, badly decayed, with illegible scribe marks visible on loose wood alongside, bears N 23°E 43.5 ft.

Description of monument and accessories established to perpetuate the original location of this corner:

At the position of the found basalt corner stone, we set a 2"x30" galvanized iron pipe, 26 inches in the ground, original basalt stone is buried along the south side of the pipe, with brass cap, marked:

From which we mark new bearing trees:

- A 10" Douglas Fir, scribed "1/4 S 27 BT" on a double blaze bears N 87°W 2.7 ft., and a 10" Western Larch, scribed "1/4 S 34 BT" on a double blaze bears S 37°E 9.8 ft.

Attached brass washer marked "LS 1099" to lower blaze of new BT's.

T5S R38E
S 27
1/4 —+—
S 34
PLS 1099
1984

Magnetic Compass (20° East Declination)
Steel Tape

October 9, 1984

Witnesses:

Gary Langlitz, LS 1099
Ray Crapo
Doug Wright



UNION COUNTY SURVEYOR
Date Received <u>11-13-84</u>
Date Filed <u>11-13-84</u>
By <u>G. LANGLITZ, DEPUTY</u>
File No. <u>1022-84 R</u>

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 19.....
..... by
(COUNTY OFFICIAL) (DEPUTY)