


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

This $\frac{1}{4}$ corner was set by deputy surveyor W.B. Barr, under Contract No. 388, dated May 7, 1881. He states he set a marked basalt stone 12" x 10" x 5"; from which:
 A pine 4" dia. bears N 09 W, 58 lks. dist.
 A willow 3" dia. bears S 64 W, 78 lks. dist.



Description of corner evidence found:

At the assumed $\frac{1}{4}$ corner location, I found a basalt stone 14" x 10" x 7" with $\frac{1}{4}$ marked on the north face and being tipped to the south and mostly covered with grass and sod. I found no acceptable evidence of either of the bearing trees.

Description of monument and accessories I established to perpetuate the original location of this corner:

With the marked stone closely agreeing to the GLO description, I accepted the center of the hole left by the stone as being the true $\frac{1}{4}$ corner. I then set an Alum. cap on a 2" x 30" pipe, with a magnet fixed in the cap, at the corner location. I buried the pipe flush with the surface of the ground. I then placed the marked stone upside down, with the $\frac{1}{4}$ marking facing the monument on the west side of the monument and buried below the surface of the ground. From which I set two new bearing trees:
 A pine 11" dia. bears N 25 30 W, 48.24 feet and scribed $\frac{1}{4}$ S S 26 BT.
 A pine 8" dia. bears S 72 37 E, 18.61 feet and scribed $\frac{1}{4}$ S S 35 BT.

**UNION COUNTY
SURVEYOR**

Date Received 9-22-87

Date Filed 9-25-87

By G. LANGLITZ, Deputy

File No. 123-87 R

REGISTERED
PROFESSIONAL
LAND SURVEYOR

James H. Hambleton

9-25-87

OREGON
JULY 10, 1964
JAMES H. HAMBLETON
645

REFER TO SURVEY 28-87

Office of..... County of.....
 State of....., I hereby certify that the within instrument was filed in this office
 for record on the..... day of....., 19.....
 by
 (COUNTY OFFICIAL) (DEPUTY)