

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:


Original survey by W.B. Barr under Contract No. 388, dated May 7, 1881.

Marked a basalt rock, 16"x10"x8" for 1/4 Sec. corner from which:

A Pine 36" in diam. bears S80°E, 19 lks. dist.

A pine 30" in diam. bears S15°W, 55 lks. dist.

X-13



Description of corner evidence found:

At the corner position found 16"x10"x8" solidly set on side of hill, no visible markings, from which the remains of the original bearing trees:

A sawn off Ponderosa Pine stump, slightly decayed with just the bottom of a blaze showing, bears S80°E, 12.5 feet,

A dead, down and leaning lower section of a Ponderosa Pine, badly decayed, stump hole bears S15°W, 36.0 feet.

Description of monument and accessories I established to perpetuate the original location of this corner:

At the position of the basalt rock, set a No.5 x 30" rebar with yellow plastic cap marked "PLS 699", original basalt rock is buried alongside, north of monument,


new reference trees established:

An 8" Ponderosa Pine bears N18°E, 69.00 feet,

An 11" Ponderosa Pine bears N88°E, 16.10 feet,

A 6" Ponderosa Pine bears S27°E, 21.10 feet,

An 8" Ponderosa Pine bears S72°W, 22.90 feet.



Attached a 1-1/2" Aluminum washer stamped "PLS 699" to base side center of tree with a 60d nail.

Compass Declination 19-1/2° East

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 9, 1965
LELAND LEE MYERS
699

Renewal Date 1/1/17

UNION COUNTY
SURVEYOR

Date Received 10/14/15

Date Filed 10/14/15

By Bill G. Meier

File No. 145-2015R