


**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

**History of original corner establishment:**

This section corner was set by deputy surveyor D. P. Thompson, under Contract No. 103, dated Sept. 3 1863. He states he set a post for section corner to Sec's 19, 20, 29 & 30 in a mound of earth with charred stake and pits and trenches as per instruction.



**Description of corner evidence found:**

At the assumed section corner location I found a large rock jack at an ancient fence intersection. In the north-west corner of the rock jack and under the base I bound evicence being a small circle of stone in place as if set around a post. I found no trace of the charred stake.

**Description of monument and accessories I established to perpetuate the original location of this corner:**

With no other evidence available and the corner position appears correct by survey, I accepted the center of the small mound of stone as being the true section corner. I then set an Alum. cap on a 2" x 30" pipe, with a magnet fixed in the cap, at the corner location. I buried the pipe to within 6" above the surface of the ground. I then rebuilt the old rock jack covering the monument. There are no bearing trees available in the vicinity of this corner.

<b>UNION COUNTY SURVEYOR</b>
Date Received <u>9-22-87</u>
Date Filed <u>9-25-87</u>
By <u>G. LANGLITZ, DEPUTY</u>
File No. <u>115-87 R</u>

REGISTERED PROFESSIONAL LAND SURVEYOR
<i>James H. Hambleton</i>
<u>9-25-87</u>
OREGON JULY 10, 1964 JAMES H. HAMBLETON 645

REFER TO SURVEY 28-87

Office of..... County of.....  
 State of....., I hereby certify that the within instrument was filed in this office  
 for record on the..... day of....., 19.....  
 ..... by .....  
 (COUNTY OFFICIAL) (DEPUTY)