## CERTIFIED RECORD OF LAND CORNER MONUMENTATION

## History of original corner establishment:

This  $\frac{1}{4}$  cor. was set by deputy surveyor Timothy W. Davenport, under Contract No. 102, dated July 20, 1863. He states he set a quarter section post, made mound of earth and drove charred stake. With a spring branch 2.75 chains north of corner.

A retracement survey by deputy surveyor W. B. Barr under Contract No. 388, dated May 7, 1881 in which Mr. Barr states this corner was in a ploughed field and there was no trace of the corner. He re-established the corner by setting a post in a raised mound of rock as per instructions.

DIAGRAM
T 5 S
R 38 E R 39 E
\$\frac{1}{4}\$
S 36 | S 31
\$1987
ORLS 645

## Description of corner evidence found:

At the assumed  $\frac{1}{4}$  cor. location I found a field to have been farmed for many years and now is being used only as pasture land. There was no trace of the  $\frac{1}{4}$  cor. set by Mr. Barr. I found the spring branch to be located at 42.75 chains as per the GLO topographic calls, and was able to restore the  $\frac{1}{4}$  corner to its original position using the line established between the township corner and the found  $\frac{1}{4}$  corners common to Sec's. 25 & 30 and Sec's 24 & 19.

## Description of monument and accessories I established to perpetuate the original location of this corner:

With no other evidence available and the corner position appears correct by survey, I accepted the restored position as the true  $\frac{1}{4}$  corner. I then set an Alum. cap on a 2" x 30" pipe with a magnet fixed in the cap, at the corner location. I buried the monument 8" below the surface and placed four pieces of metal from an antique car and one plow shear in the hole along side the monument to enable locating the monument with a metal detector. I then placed a sand stone 18" x 8" x 7" over the top of the monument, and marked  $\frac{1}{4}$  on the west face. This stone is only to assist in locating the monument. There are no bearing trees available in the vicinity of this corner.

	UPICA COUNTY SURVEYOR	REGISTERED
	Pate Received 9-22-87	PROFESSIONAL LAND SURVEYOR
	Data Filed 9-25-87	9-25-87
	G. LAUGLITZ DEPUTY	JAMES H. HAMBLETON
	7a No. 146-87 R	645
Re	CER TO SURVEY 28-8	37
Office of	County of	
State of / hereby of		
for record on the day of		
(COUNTY OFFICIAL)	by	